



LED signal light white black glossy - Light signal for switching device None 29532045



Berker
29532045
4011334414605 EAN/GTIN

69,71 USD excl. VAT**
plus shipping



15-16 days* (USA)

LED signal light white black glossy 29532045 Composition of basic element with central cover plate, number of modules (with modular design) 0, lampholder without, with illuminant, illuminant LED not interchangeable, with interchangeable symbol, use as button no, type of installation flush-mounted, material other, material quality other, Halogen-free, Surface untreated, Glossy surface finish, Color black, RAL number (similar) 9005, Lamp color white, Suitable for degree of protection (IP) IP20, Rated voltage 230V, Max. lamp power 1W, LED signal light, white lighting R.1/R.3 black, shiny. R.1 Program description Long text Switch program made of thermoplastic, unbreakable and impact-resistant, in the colors polar white (RAL 9010), black (RAL 9005), frame 1-way to 5-way, can be used vertically and horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface. Round rockers/covers with a diameter of 58mm. Alternatively: switch range made from a 7 mm high thermoplastic carrier with a 3 mm glass surface on it, scratch-resistant, in the colors polar white (RAL 9010), black (RAL 9005), frame 1x to 5x, vertical like can be used horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface. Round rockers/covers with a diameter of 58 mm. Alternatively: Switch range made from a 7 mm high thermoplastic carrier with a 3 mm metal surface on it made of stainless steel or aluminium, impact-resistant and unbreakable, frame 1-gang to 5-gang, can be used vertically and horizontally. The socket center pieces and many other center pieces form an edgeless surface with the frame. Square basic shape and round corners 12 mm radius. With flat geometry and glossy surface. Round rockers/covers with a diameter of 58 mm. Installation devices can be used in some cases with a separate sealing set that is water-protected UP IP 44. Possibility of labeling with frames that can be labeled, abrasion-resistant labeling of the products with printing. Can be illuminated according to workplace regulations. The material used is halogen-free and UV-stable, the surfaces are easy to clean and are resistant to disinfectants. Over 150 applications.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

