



LED rotary dimmer standard - Dimmer flush mounted 3...210VA 1730 DD



Jung
1730 DD
4011377166974 EAN/GTIN

52,43 USD excl. VAT**
plus shipping



4-5 days* (USA)

Standard 1730 DD LED rotary dimmer, composition of the basic element, rotary/push button operation, phase control dimming, trailing edge phase cut dimming, load type other, light value memory, type of installation flush-mounted, type of fastening claw/screw fastening, material other, material quality other, halogen-free, nominal voltage 230 ... 230V, Frequency 50 ... 60Hz, rated power 3 ... 210VA, connection type screw terminal, core cross section 0.5 ... 4mm², rotary dimmer standard LED, insert, with incremental encoder, rated voltage: AC 230 V ~, mains frequency: 50/60 Hz, standby -Power: approx. 0.35 W, power loss: approx. 2 W, device works according to the leading edge or trailing edge principle, device can be operated without a neutral conductor, automatic setting of the dimming principle suitable for the load, switching on by soft start that protects the lamp, switching on with the last set Brightness or saved switch-on brightness, switch-on brightness can be saved permanently, minimum brightness can be saved permanently, electronic short-circuit protection with permanent shutdown after 7 seconds at the latest, electronic overtemperature protection, connected load at 25 °C: incandescent lamps: 20 to 210 W, HV halogen lamps: 20 to 210 W, HV LED lamps dimmable: typically 3 to 60 W, compact fluorescent lamps dimmable : typically 3 to 60 W, electronic transformers: 20 to 210 W, electronic transformers with LV LED 20 to 60 W, inductive transformers: 20 to 210 VA, inductive transformers with LV LED 20 to 60 VA, ohmic-capacitive: 20 up to 210 W, capacitive-inductive: not permitted, ohmic-inductive: 20 to 210 VA, ohmic and HV-LED: typically 3 to 60 W, ohmic and compact fluorescent lamps: typically 3 to 60 W, operation without neutral conductor: minimum load 50 W, does not apply to loads with HV LED and compact fluorescent lamps, power can be expanded using power boosters, total length of load line: maximum 100 m, connection: screw terminals, 1 x 0.5 to 4 mm² or 2 x 0.5 to 2.5 mm² (solid and finely stranded without ferrule) and 1 x 0.5 to 4 mm² or r 2 x 0.5 to 1.5 mm² (finely stranded with ferrule), ambient temperature: - 5 to + 45 °C, test mark: VDE, for switching and dimming lighting

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

