

Item Number EB16408161

https://www.eibabo.us/jung/led-rotary-dimmer-universal-dimmer-flush-mounted-3...420va-1731-dd-eb1 6408161



LED rotary dimmer universal - Dimmer flush mounted 3...420VA 1731 DD

×

Jung 1731 DD 4011377166981 EAN/GTIN

72,17 USD excl. VAT**

plus **shipping**



4-5 days* (USA)

Universal 1731 DD LED rotary dimmer, composition of the basic element, rotary/push button operation, phase control dimming, trailing edge phase cut dimming, universal load type, extension input, light value memory, flush-mounted type of installation, type of attachment claw/screw attachment, other material, other material quality, halogen-free, rated voltage 230... 230V, frequency 50 ... 60Hz, rated power 3 ... 420VA, connection type screw terminal, core cross section 0.5 ... 4mm², universal LED rotary dimmer, insert, with incremental encoder and extension input, rated voltage: AC 230 V ~, mains frequency: 50/60 Hz, standby power: approx. 0.35 W, power loss: approx. 4 W, device works according to the leading or trailing edge principle, device can be operated without a neutral conductor, automatic or manual setting of the dimming principle suitable for the load, LED display the set operating mode, switching on by means of a soft start that protects the lamp, switching on with the last brightness setting or saved switching on Brightness, switch-on brightness can be saved permanently, minimum brightness can be saved permanently, electronic short-circuit protection with permanent shutdown after 7 seconds at the latest, electronic overtemperature protection, connected load at 25 °C: Incandescent lamps: 20 to 420 W, HV halogen lamps: 20 to 420 W, HV LED lamps dimmable: typically 3 to 100 W, compact fluorescent lamps dimmable: typically 3 to 100 W, electronic transformers: 20 to 420 W, electronic transformers with LV LEDs 20 to 100 W, inductive transformers: 20 to 420 VA, inductive transformers with LV LEDs 20 to 100 VA, ohmic-capacitive: 20 to 420 W, capacitive-inductive: not permitted, ohmic-inductive: 20 to 420 VA, ohmic and HV-LED: typically 3 to 100 W, ohmic and compact fluorescent lamps: typically 3 to 100 W, power can be expanded using power boosters, total length of load line: maximum 100 m, connection: screw terminals, 1 x 0.5 to 4 mm² or 2 x 0.5 to 2.5 mm² (single-wire and fine-wire without ferrule) and 1 x

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

