



## LED outdoor spotlight 28W 106Gr - Downlight/spot/floodlight 1x23W 721714.1131.1



**RZB**  
721714.1131.1  
4051859012061 EAN/GTIN

**175,42 USD** excl. VAT\*\*  
plus shipping



15-16 days\* (USA)

LED outdoor spotlight 28W 4000K 106Gr 721714.1131.1 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for pedestal/floor mounting, Adjustability not adjustable, Light source LED not replaceable, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Surface powder-coated, housing color anthracite, cover material transparent glass, type of voltage AC, nominal voltage 220 ... 240V, control gear LED control gear, current-controlled, with control gear, without dimming function, highly specular reflector, light distributor reflector, symmetrical light distribution, beam angle unshielded/diffuse, light emission direct, Rated service life L80/B10 at 25 °C 50000h, degree of protection (IP) IP65, degree of protection (NEMA) other, impact resistance IK07, protection class I, rated ambient temperature according to IEC62722-2-1 -25 ... 50°C, suitable for lamp power 23 .. 23W, maximum system power 23W, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous flux 2250 ... 2250lm, rated luminous flux according to IEC 62722-2-1 2250lm, lamp luminous efficacy 98lm/W, power factor 0.95, width 109mm, height/depth 226mm, length 194mm, type of wiring termination, number of poles 3, conductor cross section 2.5mm², connectable conductor cross section 2.5 ... 2.5mm², connection type plug-in terminal, luminaire with limited surface temperature "D mark", luminous efficacy of luminaire 98lm/W, glow wire test according to IEC 60695-2-11 960 °C - 30 s, photobiological safety according to EN 62471 RG1, color consistency (McAdam ellipse) SDCM3, Made in Germany. 3 different light distributions: Narrow Spot, Medium Spot and Flood. Stationary installation or mobile with plug and 5 m connecting cable. Seawater resistant coating optionally available. Ground spike set as an accessory. Central battery emergency light option available. Second cable inlet for looping through. Reduced connected load with the same luminous flux of the switchable version to save energy. Control gear on/off. Light color 840. LED service life 50,000 h (L80, B10). Pole and wall mounting accessories available. Housing made of corrosion-resistant die-cast aluminum for outdoor use, powder-coated. Bracket aluminum powder-coated. Cover clear safety glass (ESG), ceramic coated. COB-LED with interchangeable socket. Reflector of pure aluminum, high-gloss anodised. Standard with diaphragm valve to prevent condensation. With plug-in connection terminal 3x 2.5 mm². Suitable for cable diameters up to d 13 mm. Second cable bushing for network forwarding as an accessory.

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

