



LED spotlight 14W 3000K - Ceiling-/wall luminaire 1x11W OL WL100 OP800 830BK



ESYLUX
OL WL100 OP800 830BK
EL10710711
4015120710711 EAN/GTIN

84,03 USD excl. VAT**
plus shipping

 **15-16 days* (USA)**

Ceiling-/wall luminaire 1x11W, Suitable for wall mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting no, Suitable for recessed mounting no, Suitable for surface mounting yes, Illuminant LED not interchangeable, With illuminants yes, Suitable for light band configuration no, Suitable for number of lamps 1, Lamp holder other, Material of the housing Aluminum, Housing color black, Material of the cover Glass opal, Type of grid without, Voltage AC, Rated voltage 230V, Operating device LED operating device current-controlled, With operating device yes, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming Potentiometer (device-integrated) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Dimming dependent on control gear no, Without dimming function yes, light distributor Diffuser lens / optics / panel, Light distribution symmetrical, Beam angle wide beam 41-80, Light outlet directly, Rated service life L70/B10 at 25 °C 80000 h, Rated service life L70/B50 at 25 °C 100000 h, Rated service life L80/B10 at 25 °C 50000 h, Rated service life L80/B50 at 25 °C 65000 h, Rated service life L90/B10 at 25 °C 25,000 h, Rated service life L90/B50 at 25 °C 30000 h, Degree of protection (IP) IP55, Protection class II, Suitable for emergency light no, With motion detector no, With light sensor no, With louvers no, Suitable for lamp power 11 W, Max. System performance 14W, Rated luminous flux according to IEC 62722-2-1 750 lm, Light color white, Color temperature 3000K, Color rendering index CRI 80-89, luminous efficacy 53 lm/W, Width 104 mm, Height/depth 143 mm, Length 205 mm, Number of poles 3, Conductor cross-section 2.5 mm², Connection type Plug-in terminal

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

