



**LED spotlight ADF with black mounting bracket -
Downlight/spot/floodlight SUN OFL TR1000 830BK**



ESYLUX
SUN OFL TR1000 830BK
EL10810015
4015120810015 EAN/GTIN

46,79 USD excl. VAT**
plus shipping



4-5 days* (USA)

Spot light/floodlight, Suitable for surface mounting yes, Suitable for recessed mounting no, Suitable for wall mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting no, Suitable for truss mounting no, Suitable for pedestal/floor mounting no, Suitable for track mounting no, Suitable for clamp mounting no, Suitable for rope system no, Adjustability rotatable and swiveling, With motion detector no, With light sensor no, Illuminant LED not interchangeable, With illuminants yes, Suitable for number of lamps 1, Lamp holder without, Material of the housing Aluminum, Surface powder-coated, Housing color black, Material of the cover Glass transparent, Surface brushed no, Voltage AC, Rated voltage 230V, LED rated current at constant current 40..48 mA, Operating device LED operating device current-controlled, With operating device yes, Dimming dependent on control gear no, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming Potentiometer (device-integrated) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function yes, Reflector without, light distributor Diffuser lens / optics / panel, Light distribution symmetrical, Beam angle extremely wide beam > 80 °, Light outlet directly, Rated service life L70/B10 at 25 °C 45,000 h, Rated service life L70/B50 at 25 °C 45,000 h, Rated service life L80/B10 at 25 °C 30000 h, Rated service life L80/B50 at 25 °C 30000 h, Rated service life L90/B10 at 25 °C 15000 h, Rated service life L90/B50 at 25 °C 15000 h, Degree of protection (IP) IP65, Protection class I, Max. System performance 9 W, Light color white, Color temperature 3000K, Color rendering index CRI 80-89, Luminous flux 950 lm, Rated luminous flux according to IEC 62722-2-1 950 lm, Width 133 mm, Height/depth 75 mm, Length 150 mm, Number of poles 3, Conductor cross-section 2.5 mm², Connectable conductor cross-section 1.5..2.5 mm², Connection type Screw terminal, luminous efficacy 105 lm/W

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

