



**LED spotlight ADF 5000K with black mounting bracket -  
Downlight/spot/floodlight SUN OFL TR3700 850BK**



**ESYLUX**  
SUN OFL TR3700 850BK  
EL10810169  
4015120810169 EAN/GTIN

**112,74 USD** excl. VAT\*\*  
plus shipping



4-5 days\* (USA)

Spot light/floodlight, Suitable for surface mounting yes, Suitable for recessed mounting no, Suitable for wall mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting no, Suitable for truss mounting no, Suitable for pedestal/floor mounting no, Suitable for track mounting no, Suitable for clamp mounting no, Suitable for rope system no, Adjustability rotatable and swiveling, With motion detector no, With light sensor no, Illuminant LED not interchangeable, With illuminants yes, Suitable for number of lamps 1, Lamp holder without, Material of the housing Aluminum, Surface powder-coated, Housing color black, Material of the cover Glass transparent, Surface brushed no, Voltage AC, Rated voltage 230V, LED rated current at constant current 125..273 mA, Operating device LED operating device current-controlled, With operating device yes, Dimming dependent on control gear no, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming Potentiometer (device-integrated) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function yes, Reflector without, light distributor Diffuser lens / optics / panel, Light distribution symmetrical, Beam angle extremely wide beam > 80 °, Light outlet directly, Rated service life L70/B10 at 25 °C 45,000 h, Rated service life L70/B50 at 25 °C 45,000 h, Rated service life L80/B10 at 25 °C 30000 h, Rated service life L80/B50 at 25 °C 30000 h, Rated service life L90/B10 at 25 °C 15000 h, Rated service life L90/B50 at 25 °C 15000 h, Degree of protection (IP) IP65, Protection class I, Max. System performance 28 W, Light color white, Color temperature 5000K, Color rendering index CRI 80-89, Luminous flux 3650 lm, Rated luminous flux according to IEC 62722-2-1 3650 lm, Width 227 mm, Height/depth 86 mm, Length 252 mm, Number of poles 3, Conductor cross-section 2.5 mm², Connectable conductor cross-section 1.5..2.5 mm², Connection type Screw terminal, luminous efficacy 130 lm/W

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

