

Item Number EB11573191

25.04.2024/00:04

×

https://www.eibabo.us/zumtobel/led-surface-mounted-ceiling-light-2600-830-q-ldo-ceiling-wall-luminair e-mirel-l-a-42925613-eb11573191

## LED surface-mounted ceiling light 2600-830 Q LDO -Ceiling-/wall luminaire MIREL-L A #42925613

Zumtobel MIREL-L A #42925613 42925613 9008709654617 EAN/GTIN

348,93 USD excl. VAT\*\*

plus shipping bulky item



LED surface-mounted ceiling light 2600-830 Q LDO MIREL-L A 42925613 Suitable for ceiling mounting, Suitable for surface mounting, LED bulbs cannot be replaced, With bulbs, Suitable for computer workstations according to EN 12464-1, Suitable for number of bulbs 1, Other socket, Housing material steel, Housing color white, design of the louvre without, type of voltage AC, nominal voltage 220 ... 240V, control gear current-controlled LED control gear, with control gear, DALI dimming, light distribution symmetrical, light emission direct, rated service life L70/B50 at 25 °C 100000h, rated service life L80/B50 at 25 °C 66000h, rated service life L90/B50 at 25 °C 33000h, degree of protection (IP) IP40, protection class I, max. system power 19.5W, rated luminous flux according to IEC 62722-2-1 2630Im, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, power factor 0.9, width 600mm, height/depth 52mm, length 600mm, Flat and modular LED surface-mounted ceiling light with lens optics. Lamp power: 18.5 W, DALI controllable lamp (DALI only) with LED converter, LED service life 50,000 hours until the luminous flux arons to 85% of the initial value. Color tolerance (initial MacAdam): 3. Luminaire luminous flux: 2700 Im, luminaire luminous efficacy: 146 Im/W. Color rendering Ra > 80, color temperature 3000 K. Luminaire with symmetric wide distribution. Light control via square lens optics, glare-free light distribution with UGR < 16 and L65 < 1000 cd/m² in accordance with EN 12464-2011, low sensitivity to dirt and easy cleaning, flat luminaire housing made of sheet steel, powder-coated in white, luminaire housing with visible luminaire height of 52mm, luminaire with halogen-free wiring, dimensions: 600 x 600 x 52 mm, weight: 6.64 kg

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online



