

Item Number EB11573200

https://www.eibabo.us/zumtobel/led-downlight-3800-840-m625levg-ka-ceiling-wall-luminaire-mirel-l-lay-42182120-eb11573200



LED downlight 3800-840 M625LEVG KA - Ceiling-/wall luminaire MIREL-L LAY#42182120

×

Zumtobel

MIREL-L LAY#42182120 42182120 9008709653870 EAN/GTIN

277,55 USD excl. VAT**

plus shipping bulky item



15-16 days* (USA)

LED recessed light 3800-840 M625LEVG KA MIREL-L LAY42182120 Suitable for ceiling mounting, Suitable for built-in mounting, LED bulbs cannot be replaced, With bulbs, Suitable for computer workstations according to EN 12464-1, Suitable for number of bulbs 1, Other socket, Housing material steel, Housing color white, design of the louvre without, type of voltage AC, nominal voltage 220 ... 240V, control gear current-controlled LED control gear, with control gear, without dimming function, light distribution symmetrical, light emission direct, rated lifespan L70/B50 at 25 °C 100000h, rated lifespan L80/B50 at 25 °C 66000h, rated service life L90/B50 at 25 °C 33000h, degree of protection (IP) IP20, protection class I, max. system power 27.8W, rated luminous flux according to IEC 62722-2-1 3740lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, power factor 0.98, width 310mm, height/depth 38mm, length 1248mm, modular LED recessed ceiling light with lens optics. Luminaire output: 25.7 W, with LED converter, LED service life 50,000 hours until the luminous flux drops to 85% of the initial value. Color tolerance (initial MacAdam): 3. Luminaire luminous flux: 3750 lm, luminaire luminous efficacy: 146 lm/W. Color rendering Ra > 80, color temperature 4000 K. Luminaire with symmetric wide distribution. Light control via square lens optics, glare-free light distribution with UGR < 16 and L65 < 1000 cd/m2 in accordance with EN 12464:2011, low sensitivity to dirt and easy cleaning, luminaire with electrical connection from the outside, installation as pure lay-in luminaire for module ceilings with visible support system, housing made of sheet steel in Color white. Luminaire wired halogen-free, dimensions: 1248 x 310 x 38 mm, weight: 4.46 kg

YOUR ADVANTAGES



WORLDWIDE TRADE Corporate video eibmarkt®




COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order





DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- * Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

