

LED downlight 3600-830 M625Q LDO - Ceiling-/wall luminaire MIREL-L NIV#42925643



Zumtobel
MIREL-L NIV#42925643
42925643
9008709654914 EAN/GTIN

349,87 USD excl. VAT**
plus shipping bulky item



15-16 days* (USA)

LED built-in light 3600-830 M625Q LDO MIREL-L NIV42925643 Suitable for ceiling mounting, Suitable for built-in mounting, LED bulbs cannot be replaced, With bulbs, Suitable for computer workstations according to EN 12464-1, Suitable for number of bulbs 1, Other socket, Housing material steel, Housing color white, design of the louvre without, type of voltage AC, nominal voltage 220 ... 240V, control gear current-controlled LED control gear, with control gear, DALI dimming, light distribution symmetrical, light emission direct, rated service life L70/B50 at 25 °C 100000h, rated service life L80/B50 at 25 °C 66000h, rated service life L90/B50 at 25 °C 33000h, degree of protection (IP) IP20, protection class I, max. system power 27.4W, rated luminous flux according to IEC 62722-2-1 3620lm, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, power factor 0.95, width 623mm, height/depth 74mm, length 623mm, modular LED recessed ceiling light with lens optics. Luminaire output: 25.4 W, DALI controllable luminaire (DALI only) with LED converter, LED service life 50000 h until the luminous flux drops to 85% of the initial value. Color tolerance (initial MacAdam): 3. Luminaire luminous flux: 3670 lm, luminaire luminous efficacy: 144 lm/W. Color rendering Ra > 80, color temperature 3000 K. Luminaire with symmetric wide distribution. Light control via square lens optics, glare-free light distribution with UGR < 16 and L65 < 1000 cd/m² in accordance with EN 12464:2011, low sensitivity to dirt and easy cleaning, flat luminaire housing made of sheet steel painted in white, installation as an adjustable luminaire for cut ceiling openings and modular ceilings with concealed or visible Support system, fastening set to be ordered separately, luminaire wired without halogen, dimensions: 623 x 623 x 74 mm, weight: 6.84 kg

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

