

**LED recessed light 3600-830 M625LLDO KA - Ceiling-
/wall luminaire MIREL-O NIV#42925664**



Zumtobel
MIREL-O NIV#42925664
42925664
9008709654440 EAN/GTIN

447,94 USD excl. VAT**
plus shipping bulky item



15-16 days* (USA)

LED recessed light 3600-830 M625LLDO KA MIREL-O NIV42925664 Suitable for ceiling mounting, Suitable for recessed mounting, Light source LED not replaceable, With light source, Suitable for number of light sources 1, Other socket, Housing material steel, Housing color white, Cover material plastic transparent, design of the louvre without, type of voltage AC, nominal voltage 220 ... 240V, control gear LED control gear, current-controlled, with control gear, DALI dimming, light distribution symmetrical, light emission direct, rated service life L70/B50 at 25 °C 74000h, rated service life L80/B50 at 25 °C 50000h, rated service life L90/B50 at 25 °C 24000h, degree of protection (IP) IP20, protection class I, max. system power 28.9W, rated luminous flux according to IEC 62722-2-1 3770lm, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, power factor 0.91, width 310mm, height/depth 85mm, length 1248mm, modular LED recessed ceiling light with opal optics. Luminaire output: 27.7 W, DALI controllable luminaire (DALI only) with LED converter, LED service life 50000 h until the luminous flux drops to 80% of the initial value. Color tolerance (initial MacAdam): 3. Luminaire luminous flux: 3760 lm, luminaire luminous efficacy: 136 lm/W. Color rendering Ra > 80, color temperature 3000 K. Light control via backlit, embossed opal optics UGR < 22 in accordance with EN 12464:2011, homogeneous resolution of the LED light points, LED modules incl. highly reflective 3Dprotect(R) reflector as contact protection against damage from electrostatic discharge, removable outer cover made of PMMA for a homogeneous appearance and easy cleaning, luminaire housing made of sheet steel painted in white, luminaire with electrical connection from the outside, installation as a leveling luminaire for cut ceiling openings and modular ceilings with concealed or visible support system, fastening set must be ordered separately, Luminaire wired halogen-free, dimensions: 1248 x 310 x 85 mm, weight: 5.4 kg

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

