



Room thermostat 80x80x23mm 3 buttons - Room temperature controller 5...30°C VT D



Vitramo

VT D

4250939310039 EAN/GTIN

61,87 USD excl. VAT**

plus shipping



15-16 days* (USA)

Room thermostat 80x80x23mm 3 buttons VT D version on/off, type of power supply battery, two-wire connection, measuring range lower value 5°C, measuring range upper value 30°C, thermal feedback without, control characteristics other, heating, number of outputs heating 1, number of outputs Cooling 0, differential value 0.5 ... 0.5K, temperature can be read, resistance sensor version, surface-mounted installation, with display, operation button, type contact closer, max. voltage of the contacts 230V, max. contact load 5A, protection class (IP) IP30, degree of protection (NEMA) other, color cream white, RAL number 9010, height 80mm, width 80mm, depth 23mm, temperature controller class I, power consumption in standby mode (solstandby) 0W, digital room thermostat for heating control as a wall device. Accurate temperature control. 3 buttons. Operating mode: comfort, economy, frost protection, off. Ease of use. control range limitation. In order to optimally plan the Vitramo heating system, it is not only designed according to DIN EN 12831, but also adapted to the special conditions of the building. Already during the planning phase, a building is divided into rooms, demand zones and heating areas depending on its size and use. A demand zone represents a space/space defined by its specific type of use and conditions such as cooling, ventilation, humidity, etc. Every room needs a room thermostat to regulate the air temperature. Wire-guided room thermostats as room temperature controllers are wired directly to a heating element or connected via the DS-P control unit. Due to the structural conditions, these devices are often used in new buildings or as part of a renovation. If the installed power exceeds the specified switching capacity of the respective room thermostat, then the heating elements must be switched via additional load relays type LS-E. In any case, the life of the room thermostat will be extended if a load relay does the work.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

