

## Item Number EB12902050

https://www.eibabo.us/siemens/contactor-for-railway-18.5kw-400v-magnet-contactor-40a-24vdc-3rt203 5-3xb44-0la2-eb12902050



## Contactor for railway, 18.5kW/400V - Magnet contactor 40A 24VDC 3RT2035-3XB44-0LA2

×

## Siemens

3RT2035-3XB44-0LA2 4011209942394 EAN/GTIN

238,82 USD excl. VAT\*\*

plus **shipping** 



15-16 days\* (USA)

Contactor for railway, 18.5kW/400V 3RT2035-3XB44-0LA2 Rated control supply voltage Us at DC 24 ... 24V, type of voltage for actuation DC, rated operational current le at AC-1, 400 V 60A, rated operational current le at AC-3, 400 V 40A, rated operational power at AC-3, 400 V 18.5kW, rated operational current le at AC-4, 400 V 35A, rated operational power at AC-4, 400 V 18.5kW, rated operational power NEMA 22.0649625kW, suitable for series installation, number of auxiliary contacts as NO contacts as NO contact 2, number of auxiliary contacts as NC contact 2, connection type main circuit screw connection, number of NC contacts as main contacts 0, number of NO contacts as main contacts 3, railway contactor, AC-3 40 A, 18.5 kW / 400 V 2 NO + 2 NC DC 24 V, 0.7-1.25\* US, with varistor, 3-pole, size S2, spring-loaded connection SIRIUS 3RT2 contactor for switching motors under extreme conditions, e.g. for railway applications. The 3RT2 contactors are part of the SIRIUS modular system with its optimal coordinated products. They impress with their high performance combined with a compact design and high contact reliability. They can be combined with other components in the load feeder in a variety of ways. Many of the device combinations are tested at the factory. The contactors offer the optimal connection to the controller for every application (parallel, via ASi or IO-Link). Integrated auxiliary switches reduce the complexity of your structure. The front connections enable easy wiring. The 3RT2 contactors are climate-proof, approved worldwide (eg IEC and UL/CSA) and IE3/IE4ready. This variant is characterized by an extended working and temperature range for tougher environmental conditions. They are available in different sizes and in a large power range with AC and DC operation. In addition to screw connection technology, the devices are also consistently available with spring-loaded connections for a fast, maintenance-free and vibration-proof connection. The comprehensive range of accessories, such as auxiliary switc

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

