



https://www.eibabo.us/siemens/push-button-metal-red-push-button-push-button-actuator-red-ip67-ip69 k-3su1250-0eb20-0aa0-eb12904088



Push button metal, red, push button - Push button actuator red IP67/IP69K 3SU1250-0EB20-0AA0

×

Siemens

3SU1250-0EB20-0AA0 4011209973930 EAN/GTIN

16,49 USD excl. VAT**

plus **shipping**



15-16 days* (USA)

Push button metal, red, push button. 3SU1250-0EB20-0AA0 Color of the button red, number of command points 1, design of the lens round, hole diameter 22.3mm, width of the opening 29.5mm, height of the opening 20.3mm, design of the button other, momentary, with front ring, material of the front ring metal, front ring color chrome, degree of protection (IP), on the front IP67/IP69K, NEMA degree of protection, on the front other, pushbutton, compact, with extended stroke (12 mm), 22 mm, round, metal, red, pushbutton, flat, Momentary contact, with SIRIUS ACT pushbutton holder for switching and controlling electrical loads. Under the SIRIUS ACT brand name, Siemens offers a unique portfolio of commanding and signaling devices with global product approvals in four modern design series made of robust real metal and high-quality plastic. The innovative snap-on concept simplifies assembly to such an extent that only one hand and no special tools are required. Groove-free holes are sufficient as mounting holes, as 100% anti-twist protection is already integrated. Thanks to the consistently high degree of protection, the robust devices are suitable for industrial use and for outdoor use. Even cleaning with a high-pressure jet is possible. Neither dust, oil nor aggressive alkalis can disrupt reliable operation. In addition to the standard wiring, the devices can also be connected to the controller via PROFINET, AS-Interface or IO-Link. This reduces your wiring effort, minimizes sources of error and gains more flexibility. The graphic online configurator provides convenient support when selecting and ordering individual devices, housings and labels. Extensive documentation (e.g. manual, 3D data, connection diagram) is available. Available versions: several colours, illuminated/non-illuminated, with/without labeling, latching/momentary actuation, various push button and front ring heights. Note: compact device with mechanical switching function, can only be used with an extension plunger (3SU1900-0KG10-0AA0). Delivery includin

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

