



Contactor 22kW/400V, 2NO+2NC - Magnet contactor 51A 48...80VAC 3RT2036-1NE34



Siemens
3RT2036-1NE34
4047621003474 EAN/GTIN

253,04 USD excl. VAT**
plus shipping



15-16 days* (USA)

Contactor 22kW/400V, 2NO+2NC 3RT2036-1NE34 Rated control supply voltage Us at AC 50 Hz 48 ... 80V, Rated control supply voltage Us at AC 60 Hz 48 ... 80V, Rated control supply voltage Us at DC 48 ... 80V, Type of voltage for actuation AC/ DC, rated operational current Ie at AC-1, 400 V 70A, rated operational current Ie at AC-3, 400 V 51A, rated operational power at AC-3, 400 V 22kW, rated operational current Ie at AC-4, 400 V 41A, rated operational power at AC-4, 400 V 22kW, rated operational power NEMA 29.41995kW, suitable for series installation, number of auxiliary contacts as NO 2, number of auxiliary contacts as NC 2, connection type main circuit screw connection, number of NC as main contacts 0, number of NO as main contacts 3, power contactor, AC -3 50 A, 22 kW / 400 V 2 NO + 2 NC, AC / DC with varistor, 3-pole, size S2, screw connection SIRIUS 3RT2 power contactor for switching motors. The 3RT2 contactors are part of the SIRIUS modular system with its perfectly matched products. They impress with their high performance combined with a compact design and high contact reliability. They can be combined with other components in the load feeder in a variety of ways. Many of the device combinations are tested at the factory. The contactors offer the optimal connection to the controller for every application (parallel, via ASi or IO-Link). Integrated auxiliary switches reduce the complexity of your structure. The front connections enable easy wiring. The 3RT2 contactors are climate-proof, approved worldwide (eg IEC and UL/CSA) and IE3/IE4ready. They are available in various sizes and in a large power range with AC and DC operation. In addition to screw connection technology, the devices are also consistently available with spring-loaded connections for a fast, maintenance-free and vibration-proof connection. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, etc. is the same for all sizes. The available link modules, function modules and the SIRIUS 3RV29 infeed system significantly reduce the wiring effort. The 3RT2 power contactors replace the proven 3RT1 series (up to 55 kW). Simple, efficient, always up-to-date - the SIRIUS modular system.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

