



Motor protection circuit-breaker 32A 3RV2131-4EA10


Siemens

3RV2131-4EA10

4011209930414 EAN/GTIN

192,31 USD

excl. VAT**

plus shipping



15-16 days* (USA)

Circuit breaker 32A 3RV2131-4EA10 overload release current setting 22 ... 32A, setting range of the instantaneous short-circuit release 416 ... 416A, with thermal protection, sensitive to phase failure, magnetic tripping technology, rated operational voltage 690 ... 690V, rated uninterrupted current I_u 32A, rated operational power at AC-3, 230 V 7.5kW, rated operational power at AC-3, 400 V 15kW, connection type main circuit screw connection, design of the actuating element rotary knob, device type built-in device fixed installation technology, number of poles 3, rated limiting short-circuit breaking current I_{cu} at 400 V, AC 65kA, protection class (IP) IP20, height 140mm, width 75mm, depth 149mm, circuit breaker size S2 for motor protection, CLASS 10 with overload relay function A release 22...32 A N release 416 A screw connection, standard switching capacity SIRIUS 3RV2 circuit breaker for motor protection with overload relay function for safe disconnection in the event of a short circuit and consumer protection and system against overload, as well as for safe disconnection of the system from the mains. The compact and climate-proof circuit breakers are optimized for use in consumer feeders due to their low waste heat, of course also for IE3/IE4 motors and equally for switching direct current. Worldwide approvals (e.g. IEC and UL/CSA) and use in potentially explosive applications (ATEX or IEC Ex) are a matter of course. Device variants are available for motor protection (also with overload relay function), system protection, short-circuit protection of starter combinations, transformer protection, as main and EMERGENCY STOP switches and for use in IT networks. They are available with a screw or spring-loaded connection for a fast, maintenance-free and vibration-proof connection, and optionally with a built-in auxiliary switch. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, signaling switches, etc., is the same for all sizes. The use of various power supply options, such as the associated SIRIUS 3RV2 infeed system, reduces the main circuit wiring considerably. The 3RV2 circuit breakers replace the tried-and-tested 3RV1 series. Simple, efficient, always up-to-date - the SIRIUS modular system.

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



DHL TRACK & TRACE

Shipment tracking



COMPLAINTS HANDLING

Obliging and 100% safely



25 YEARS OF EXPERIENCE

In worldwide mail order



ORDER LIVE CHAT

With order history



SHORT DELIVERY TIME

Warehousing



REFUND

Within 14 days



DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

