


**Power relay - Current monitoring relay AR12DX-230V**

**Eltako**
**AR12DX-230V**
**22001130**
**4010312205426 EAN/GTIN**
**41,98 USD** excl. VAT\*\*

plus shipping



4-5 days\* (USA)

Current relay AR12DX-230V Design of the electrical connection screw connection, rated control supply voltage  $U_s$  at AC 50 Hz 250 ... 250V, type of voltage for actuation AC, current measuring range 32 ... 0.1A, min. adjustable off-delay time 0s, max. permissible off-delay time 120s, number of Contacts as NC contacts 0, number of contacts as NO contacts 0, number of contacts as changeover contacts 1, width 18mm, height 58mm, depth 58mm, current relay, stand-by loss only 0.8 watts. Modular installation device for mounting on DIN rail (1 HP). Simply connect the N conductor to terminal (N) and L to 1 (L). This results in an additional stand-by consumption of only 0.1 watts. If the contact is used to control switching devices that do not switch at zero crossing themselves, (N) should not be connected, otherwise the additional closing delay will have the opposite effect. With an internal toroidal current transformer, the alternating current of 0.1A up to a maximum of 32A flowing through a consumer V1 is compared with the set value and if it is exceeded, a relay switches off a consumer V2 connected to 2 or a consumer V3 connected to 3 within 0.5 seconds. Adjustment accuracy plusminus5%. From 25A the relay always switches on. The latest hybrid technology combines the advantages of wear-free electronic control with the high performance of special relays. The current base A is set with the lower latching rotary switch A.

**YOUR ADVANTAGES**

**WORLDWIDE TRADE**
*Corporate video eibmarkt®*

**99% CUSTOMER SATISFACTION**
*> 500,000 customers worldwide*

**DHL TRACK & TRACE**
*Shipment tracking*

**COMPLAINTS HANDLING**
*Obliging and 100% safely*

**25 YEARS OF EXPERIENCE**
*In worldwide mail order*

**ORDER LIVE CHAT**
*With order history*

**SHORT DELIVERY TIME**
*Warehousing*

**REFUND**
*Within 14 days*

**DATA PROTECTION**
*Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

