×



## Item Number EB15700199

https://www.eibabo.us/eltako/multi-current-impulse-switch-1-1s.-potential-free-10a-latching-relay-esr61 m-uc-eb15700199



Multi-current impulse switch 1+1S. potential-free 10A - Latching relay ESR61M-UC

Eltako

ESR61M-UC 61200301 4010312108079 EAN/GTIN

42,61 USD excl. VAT\*\*

plus **shipping** 



4-5 days\* (USA)

Multi-current impulse switch 1+1S. potential-free 10A ESR61M-UC Other functions, type of installation flush-mounted, installation depth 58mm, number of contacts as NO contact 2, number of contacts as NC contact 0, number of contacts as changeover contact 0, control voltage 1 8 ... 230V, type of control voltage 1 AC, frequency of the control voltage 1 50 ... 50Hz, control voltage 2 10 ... 230V, type of control voltage 2 DC, frequency of the control voltage 2 50 ... 50Hz, rated switching current 16A, supply voltage 230 230V, type of voltage of the supply voltage AC/DC, max. Incandescent lamp load 2000W, max. fluorescent lamp load 1000VA, max. fluorescent lamp load (duo circuit) 1000VA, max. fluorescent lamp load (parallel compensated) 500VA, max. 1+1 NO potential-free 10A/250V AC, incandescent lamps 2000W. No standby loss. For flush mounting. 45mm long, 45mm wide, 32mm deep. The latest hybrid technology combines the advantages of wear-free electronic control with the high performance of special relays. Universal control voltage 8..230V UC. No constant power supply required, therefore no standby loss. Due to the use of bistable relays, there is no coil power loss and no heating as a result, even when switched on. The relay contact can be open or closed during commissioning and is synchronized with the first actuation. The functions of the second rotary switch are preselected with the ES/ER rotary switch. The parenthesis functions are selected with ER. You can choose between 10 functions: 2S = impulse switch with 2 NO contacts. (2R) = switching relay with 2 NO contacts. WS = impulse switch with 1 NO contact and 1 NC contact. (WR) = switching relay with 1 NO contact and 1 NC contact. SS1 = Series switch 1+1 NO contact with switching sequence 1. (RR) = Switching relay (quiescent current relay) with 2 NC contacts. SS2 = series switch 1+1 NO contact with switching sequence 2. (EW) = ON wiping relay with 1 NO contact and 1 NC contact, wiping time 1s. GS = group switch 1+1 normally open. (GR) = group relay 1+1 normally open. Switching sequence SS1: 0 - contact 1(1-2) - contact 2(3-4) - contacts 1+2. Switching sequence SS2: 0 - contact 1 - contacts 1+2 - contact 2. Switching sequence GS: 0 - contact 1 - 0 - contact 2. GR: Relay with alternately closing contact. This relay is not suitable for feedback with the switching voltage of a dimmer switch. Only use the relays ESR12DDX-UC, ESR12NP-230V+UC or ESR61NP-230V+UC for this. The electronics do not have their own power supply and therefore no power consumption in either contact position. Only during the short control pulse of only 0.2 seconds does the control current flow,...

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

\*\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

