

Stabl

×

https://www.eibabo.us/eltako/timer-2-channel-s2u12ddx-uc-eb15705680

## Timer 2-channel S2U12DDX-UC

Eltako S2U12DDX-UC 23200901 4010312603208 EAN/GTIN

## 52,53 USD excl. VAT\*\*

plus shipping



Time switch 2-channel 16A 250VAC 1+1S S2U12DDX-UC type of mounting DIN rail, number of channels 2, supply voltage 8 ... 230V, type of supply voltage AC/DC, frequency of supply voltage 50 ... 50Hz, power reserve in hours 480, Text guidance in the display, 24-hour program, weekly program, astro program, random program, quartz-controlled, contact design make contact, shortest switching time channel 1 1min, shortest switching time channel 2 1min, number of memory slots 60, automatic summer/winter time changeover, manual operation, external button input, rated switching current at 250 V AC 16A, potential-free switching contact, degree of protection (IP) IP20, width in modular units 1, width 18mm, height 82mm, depth 58mm, 2-channel time switch. 1+1 NO potential-free 16A/250V AC. With astro function. Standby loss only 0.03-0.4 watts. From production week 26/19 with display lighting. Modular installation device for mounting on mounting rail DIN-EN 60715 TH35. 1 pitch unit = 18mm wide, 58mm deep. With the patented Eltako duplex technology (DX), the normally potential-free contacts can still switch at zero crossing when switching 230V AC voltage 50Hz and thus drastically reduce wear. Simply connect the N conductor to terminal (N) and L to 1(L) and/or 3(L). This results in an additional standby loss of just 0.1 watts. Due to the use of bistable relays, there is no coil power loss and no heating as a result, even when switched on. Up to 60 timer memory location can either be occupied with the astro function (automatic switching after sunrise or sunset), the switch-on and switch-off time or a pulse switching time (at which a pulse of 2 seconds is triggered). The Astro switch-on or switch-off time can be shifted by plus/minus 2 hours. In addition, a time shift influenced by the solstices of up to plus-minus 2 hours can be entered. With control input (+A1) for central control ON or OFF with priority. Supply voltage and control voltage for the central control 8-230V UC. The timer is set using the MODE and SET buttons and a but

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

