

Item Number EB11596737

×

https://www.eibabo.us/zumtobel/led-recessed-ceiling-light-r100h-11w827230valwh-downlight-spot-floo dlight-panos-evo-60815127-eb11596737



## LED recessed ceiling light R100H 11W827230VALWH -Downlight/spot/floodlight PANOS EVO #60815127

Zumtobel PANOS EVO #60815127 60815127 4053167130109 EAN/GTIN

## 168,49 USD excl. VAT\*\*

plus shipping



LED recessed ceiling light R100H 11W827230VALWH PANOS EVO 60815127 Suitable for recessed mounting, Suitable for ceiling mounting, Adjustability not adjustable, Light source LED cannot be replaced, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Housing color white, Cover material opal plastic , Voltage type AC, Rated voltage 220 ... 240V, LED rated current at constant current 53 ... 53mA, Control gear LED control gear, current-controlled, With control gear, Without dimming function, Reflector without, Light distribution symmetrical, Light emission direct, Rated service life L70/B50 at 25 °C 100000h, rated service life L80/B50 at 25 °C 66000h, rated service life L90/B50 at 25 °C 33000h, degree of protection (IP) IP20, impact resistance IK04, protection class II, max. system power 11W, light color white, color temperature 2700 ... 2700K, Color rendering index CRI 80-89, rated luminous flux according to IEC 62722-2-1 873lm, power factor 0.9, height/depth 130mm, installation diameter 100mm, suitable for VDU workstations according to EN 12464-1, glow wire test according to IEC 60695-2-11 850 °C - 30 s, color consistency (McAdam ellipse) SDCM3, LED recessed ceiling light (complete light), "Stable White", cut-off angle 45°, fitted with: 11 W LED827, color rendering Ra > 80, color temperature 2700 K (warm white), color location tolerance (initial MacAdam): 3, luminous flux of luminaires: 873 Im, luminous efficacy of luminaires: 79 Im/W, service life: 50000h at 85% luminous flux, with ballast unit, modular, high-quality optical unit consisting of reflector and LED light chamber, integrated in the optimized heat management system made of die-cast aluminium, smooth reflector aluminium-sputtered, highly specular, iridescence-free, reflector/cover ring made of high-quality, UV Resistant polycarbonate (PC), white cover ring, mounting ring made of glass-fibre reinforced polycarbonate (PC), grey, tool-free quick assembly of the lighting unit using a bayonet catch, IP44\_IP2

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

