


**LED ceiling/wall light 4000K D675H50dimDALI - Ceiling-
/wall luminaire 1x54W 311848.000.1.76**



RZB

311848.000.1.76

4051859065197 EAN/GTIN



1215,17 USD excl. VAT**

plus shipping bulky item



15-16 days* (USA)

LED ceiling/wall light 4000K D675H50dimDALI 311848.000.1.76 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Other socket, Housing material aluminium, Housing color aluminium, Cover material Structured glass, design of the louvre without, voltage type AC, nominal voltage 230 ... 230V, control gear LED control gear current-controlled, with control gear, DALI dimming, dimming dependent on control gear, light distributor without, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct, rated service life L70/B10 at 25 °C 50000h, degree of protection (IP) IP40, degree of protection (NEMA) other, impact resistance IK02, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2-11 960 °C - 30 s, suitable for lamp power 54 ... 54W, max. system power 54W, rated luminous flux according to IEC 62722-2-1 5400lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous efficacy of luminaire 100lm/W, power factor 0.98, height/depth 50mm, outer diameter 675mm, type of wiring termination, number of poles 5, conductor cross-section 2.5mm², connection type plug-in terminal, extensive series consisting of: pendant lights. ceiling lights. wall lights. Lateral light coupling with LED. Implementation of the latest LED technology in a minimalist design. An anodized extruded aluminum profile that is only 15 mm flat holds the diffuser. Design of the unmistakable surface light with an opal/prismatic plastic diffuser or with handcrafted FerroMurano glass panes in 4 color variants. Design of the unmistakable panel light structured by diffuser glass. Painted aluminum cover. Anodised aluminum frame. Diffuser handmade colored glass FerroMurano white. Built-in operating device. Lateral light coupling with LED. Bulbs (LED) included.

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



COMPLAINTS HANDLING

Obliging and 100% safely



SHORT DELIVERY TIME

Warehousing



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



25 YEARS OF EXPERIENCE

In worldwide mail order



REFUND

Within 14 days



DHL TRACK & TRACE

Shipment tracking



ORDER LIVE CHAT

With order history



DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

