



LED ceiling/wall light 4000K D675H50dimDALI - Ceiling-/wall luminaire 1x28W 311849.000.1.76



RZB

311849.000.1.76

4051859065234 EAN/GTIN

810,15 USD excl. VAT**

plus shipping bulky item



15-16 days* (USA)

LED ceiling/wall light 4000K D675H50dimDALI 311849.000.1.76 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, LED illuminant not replaceable, With illuminant, Suitable for computer workstations according to EN 12464-1, Suitable for number of illuminants 1, Other socket, Housing material aluminium, Housing color aluminium, Cover material opal plastic, Design of the louvre without, Type of voltage AC, Nominal voltage 230 ... 230V, Control gear LED control gear, current-controlled, With control gear, Dimming DALI, Dimming dependent on the control gear, Light distributor other, Light distribution symmetrical, Beam angle unshielded /diffuse, light emission direct, rated service life L70/B10 at 25 °C 50000h, degree of protection (IP) IP40, degree of protection (NEMA) other, impact resistance IK03, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2-11 650 °C - 30 s, suitable for lamp power 28 ... 28W, max. Sy power output 31W, rated luminous flux according to IEC 62722-2-1 3450lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous efficacy of luminaire 112lm/W, power factor 0.95, height/depth 50mm, outer diameter 675mm, type of wiring Termination, 5 poles, conductor cross-section 2.5mm², connection type plug-in terminal, extensive series consisting of: pendant lights. ceiling lights. wall lights. Lateral light coupling with LED. Implementation of the latest LED technology in a minimalist design. An anodized extruded aluminum profile that is only 15 mm flat holds the diffuser. Light guide and plastic cover made of non-yellowing PMMA. Design of the unmistakable panel light by diffuser plastic (PMMA) opal. Glare rating UGR: 19.0. Versions with smart+free Bluetooth control for wireless networking and operation using an Android / iOS device, free app available for download. Tunable white versions dynamically adjustable from 2700 K to 6500 K. Light color 840. Lowest color tolerances triple MacAdam (3 SDCM). LED service life 50,000 h (L70, B10). Painted aluminum cover. Anodised aluminum frame. Diffuser plastic (PMMA) opal / microprismatic. Built-in operating device. Lateral light coupling with LED. Bulbs (LED) included.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

