

Item Number EB11597730

https://www.eibabo.us/rzb/led-ceiling-wall-light-4000k-d1040-dim.dali-ceiling-wall-luminaire-12x7-4w-31 1698.002.1.76-eb11597730

LED ceiling/wall light 4000K D1040 dim.DALI - Ceiling-/wall luminaire 12x7,4W 311698.002.1.76

RZB

311698.002.1.76 4051859079491 EAN/GTIN

1022,98 USD excl. VAT**

plus shipping bulky item



LED ceiling/wall light 4000K D1040 dim.DALI 311698.002.1.76 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Light source LED not interchangeable, With light source, Suitable for number of light sources 12, Other socket, Housing material steel, Housing color white, Cover material opal plastic, design of the louvre without, voltage type AC, nominal voltage 220 ... 240V, control gear current-controlled LED control gear, with control gear, DALI dimming, dimming dependent on control gear, light distributor without, symmetrical light distribution, beam angle unshielded/diffuse, light emission direct/indirect, rated service life L70/B10 at 25 °C 50000h, degree of protection (IP) IP44, degree of protection (NEMA) other, impact resistance IK07, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2-11 650 °C - 30 s, suitable for lamp power 7.4 ... 7.4W, max. system power 100W, rated luminous flux according to IEC 62722-2-1 10300Im, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous efficacy of luminaire 103Im/W, power factor 0.95, height/depth 230mm, outer diameter 1040mm, type of wiring termination, number of poles 5, conductor cross-section 2.5mm², connection type plug-in terminal, impressive 1040 mm diameter. In protection class IP 40 and IP 44. Diffuser made of high-quality polycarbonate or PMMA. Highly efficient LED technology. Immediate presence of light when switched on. LED lifespan 50,000 hours. Color temperature 3000 K and 4000 K. Color rendering Ra > 80. Powder-coated metal bracket. Fastening of the cover with a plastic twist lock. Cover plastic (PMMA) opal.

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online





×