



**Quantrol compact controller AC110-240V, 96x96mm -  
Temperature control relay AC 110...240V 702034/...**



**Jumo**  
702034/8-0000-23  
00605310  
4053877011842 EAN/GTIN

**279,80 USD** excl. VAT\*\*  
plus shipping

 **15-16 days\* (USA)**

Quantrol compact controller AC110-240V, 96x96mm 702034/8-0000-23 Design of the electrical connection spring-loaded connection, rated control supply voltage Us at AC 50 Hz 110 ... 240V, rated control supply voltage Us at AC 60 Hz 0V, rated control supply voltage Us at DC 0V, type of voltage for actuation AC/DC, number of measuring circuits 1, number of contacts as breakers 0, number of contacts as make contacts 1, number of contacts as changeover contacts 0, temperature measuring range -270 ... 2500°C, resistance measuring range 0 ... 4000Ohm, width 96mm, Height 96mm, depth 92.15mm. The areas of application are two-point and three-point control applications and the control of control valves. The universal analogue input for resistance thermometers, thermocouples or current/voltage signals is freely programmable. Target and actual value as well as all parameters are shown on two seven-segment LED displays (red/green) with one or two decimal places. The values can be displayed either in °C or in °F. A relay output with a switching capacity of 3 A / 230 V and 1 binary input are available. The switch position of the relay, to which different functions can be assigned, is displayed via yellow LEDs. With the binary input, e.g. B. the operation and setting locked, a ramp or timer activated or self-optimization started. The supply voltage is AC 110 to 240 V. The controller has a ramp function with an adjustable gradient for constantly changing the setpoint. In addition, a special firing curve for small ceramic kilns can be used so that controlled start-up and time-dependent firing is possible. The operator can enter target values, gradient and burning time directly on the device. As an alternative to operation from the front, the controller can be programmed via the setup program and USB interface without an additional power supply.

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler at a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

