

**Circuit breaker, 3-pole, 25A B IC60N - Miniature circuit breaker 3-p B25A A9F03325****Schneider Electric**
A9F03325
3606480439940 EAN/GTIN**27,63 USD** excl. VAT**
plus shipping

4-5 days* (USA)

Circuit breaker 3P 25A B IC60N A9F03325 tripping characteristic B, number of poles (total) 3, number of fused poles 3, rated current 25A, rated voltage 400V, rated insulation voltage Ui 500V, rated impulse withstand voltage Uimp 6kV, rated switching capacity Icn according to EN 60898 at 230 V 6kA, rated switching capacity Icn according to EN 60898 at 400 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 230 V 20kA, rated switching capacity Icu according to IEC 60947-2 at 400 V 10kA, type of voltage AC/DC, frequency 50 ... 60Hz, energy limitation class 3, overvoltage category 4, degree of pollution 3, additional equipment possible, width in module widths 3, installation depth 44.5mm, degree of protection (IP) IP20, ambient temperature during operation 35 ... 70°C, connectable conductor cross-section stranded 1 ... 16mm², connectable conductor cross-section solid 1 ... 25mm², Circuit breaker Acti 9 iC60N, 6kA (IEC/EN 60898-1), 10kA (IEC/EN 60947-2). 3-pole, rated current 25A, B characteristic, operating voltage (Ue) 380-415V AC, insulation voltage (Ui) 500V AC. Double connection terminal for cable and pin comb rail on the top and bottom of the device. Snap action for low-wear switching of the contacts. On-board insulation cover. Actuation of the DIN rail fastening element on the front of the device for tool-free assembly and easy access for the user. With mechanical error message display on the front (VisiTrip) for displaying trips due to overload or short circuit. Safe contact indicator (VisiSafe) of the miniature circuit breaker, green indicator means there is no voltage on the outgoing side. Terminals IP20, moving insulation cover. Double connection terminal from above or below. Simple removal of the individual device with the phase busbar installed, thanks to the fastening element that can be reached from the front. Technology of trip unit - thermomagnetic. Can be combined with the FI circuit breakers of the Acti 9 iID series and the FI block Vigi iC60. Additional add-on auxiliary modules (optional) - display of switch position, error tripping, shunt trip, undervoltage trip, overvoltage trip. Color RAL 9003. The iC60N miniature circuit breaker complies with the following standards - IEC/EN 60898-1 and IEC/EN 60947-2. Furthermore, this series is VDE certified!

YOUR ADVANTAGES**WORLDWIDE TRADE**
Corporate video eibmarkt®**99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide**DHL TRACK & TRACE**
Shipment tracking**COMPLAINTS HANDLING**
Obliging and 100% safely**25 YEARS OF EXPERIENCE**
In worldwide mail order**ORDER LIVE CHAT**
With order history**SHORT DELIVERY TIME**
Warehousing**REFUND**
Within 14 days**DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

