



RCD combination/RCBO - Earth leakage circuit breaker DRCBO3 C06/0,03/1N-A



Doepke
DRCBO3 C06/0,03/1N-A
09932121
4014712220683 EAN/GTIN

117,68 USD excl. VAT**
plus shipping



15-16 days* (USA)

FI/LS combination/RCBO DRCBO3 C06/0.03/1N-A number of poles (total) 2, number of fused poles 1, rated voltage 230V, rated insulation voltage U_i 440V, rated impulse withstand voltage U_{imp} 4kV, rated current 6A, rated residual current 0.03A, residual current Type A, energy limitation class 3, rated breaking capacity according to EN 61009 10kA, rated breaking capacity according to IEC 60947-2 10kA, rated short-circuit breaking capacity I_{cn} according to EN 61009-1 10kA, instantaneous switch-off characteristic, surge current strength 0.25kA, type of voltage AC, frequency 50 Hz, tripping characteristic C, overvoltage category 3, Pollution degree 2, ambient temperature during operation -25 ... 40°C, width in pitch units 2, installation depth 68mm, degree of protection (IP) IP20, connectable conductor cross-section solid 1 ... 25mm², connectable conductor cross-section stranded 1 ... 25mm², combine RCBO Residual current circuit breaker and miniature circuit breaker in one device (FI/LS combination). They protect people from fault currents and systems from short circuits and overloads. The switches of the DRCBO 3 series work independently of the mains voltage and are characterized by a high rated switching capacity. Separate displays enable a quick overview of the current operating status. DRCBO 3 can be easily installed and removed. Type A switches are pulse and AC sensitive. This function is independent of the mains voltage. Switches with tripping characteristic C are optimized for circuits with high inrush or peak currents. Standard switches are designed for circuits with a rated voltage of 230 V or 400 V and a rated frequency of 50 Hz. Properties: tripping independent of auxiliary voltage, sensitive to AC and pulsating DC residual currents (type A) small size for all rated currents, high short-circuit strength, green-red contact position indicator, residual current tripping indicator, clamping yoke terminals with protection from behind and wide terminal cross-section range for rail and cable wiring on both connection sides, neutral conductor on the right, tristable latching slide for easy installation and removal, type of installation: quick fastening on DIN rail, any installation position, any supply, areas of application: protection of circuits in residential and commercial buildings as well as industrial plants with TN-S and TN-CS networks. In IT networks, RCBOs can be provided to switch off in the event of a second earth fault. Use in systems with TN-C networks and to protect circuits is excluded. in which power electronics equipment can cause smooth DC fault currents or fault currents with...

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

