

Item Number EB12702318

×

https://www.eibabo.us/siemens/load-break-switch-160a-3-pole-size-2-safety-switch-3-p-90kw-3kd3430 -0ne10-0-eb12702318



## Load-break switch 160A, 3-pole, size 2 - Safety switch 3-p 90kW 3KD3430-0NE10-0

Siemens 3KD3430-0NE10-0 4001869472409 EAN/GTIN

118,98 USD excl. VAT\*\*

plus shipping

15-16 days\* (USA)

Load-break switch 160A, 3-pole, size 2 3KD3430-0NE10-0 Design as a main switch Design as a maintenance/repair switch Design as a safety switch Design as an EMERGENCY STOP device Number of switches 1 Max. rated operating voltage Ue at AC 1000V Rated uninterrupted current lu 160A, rated uninterrupted current at AC-23, 400 V 160A, rated short-time withstand current low 4kA, rated operational power at AC-23, 400 V 90kW, switching capacity at 400 V 90kW, number of poles 3, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as changeover contact 4, device type built-in device, fixed installation, suitable for distribution board installation, suitable for intermediate installation, color of the actuating element without, connection type main circuit blade terminal connection, degree of protection (IP), on the front IP00, degree of protection (NEMA) other, switch disconnector 160A, size. 2, 3-pole front drive on the left Basic device without handle Flat connection incl. phase barriers 3KD switch disconnectors up to 1600 A as a powerful main EMERGENCY STOP or repair switch. 3KD switch-disconnectors up to 1600 A from Siemens offer reliable personal protection and ensure high system availability in industry, infrastructure and buildings. As the main EMERGENCY STOP or repair switch, 3KD switch disconnectors reliably switch electrical equipment under load and offer a safety disconnection function and distance in low-voltage circuits. 1. Reliable protection against electrical accidents. 2. Robust technology for high system availability. 3. Versatile in use with variable connection and drive types. 4. Easy retrofitting of additional functions with a wide range of accessories. 5. Fast mounting on the DIN rail for sizes up to 200 A. 6. Efficient engineering thanks to extensive CAx data. 7. Uncomplicated documentation with the manual configurator. 8. Suitable for wind power and solar power systems. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers an integrated po

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

