

×

https://www.eibabo.us/siemens/simatic-connection-temperature-range-fieldbus-communication-module -6es7153-2ba70-0xb0-eb15507281

Simatic connection temperature range - Fieldbus communication module 6ES7153-2BA70-0XB0

Siemens

6ES7153-2BA70-0XB0 4047623404217 EAN/GTIN

837,85 USD excl. VAT**

plus shipping

📙 15-16 days* (USA)

SIMATIC connection Temperature range 6ES7153-2BA70-0XB0 supply voltage at AC 50 Hz 0V, supply voltage at AC 60 Hz 0V, supply voltage at DC 20.4 ... 28.8V, voltage type of the supply voltage DC, supports protocol for PROFIBUS, system component, degree of protection (IP) IP20, with electrical isolation, fieldbus connection possible via separate bus coupler, DIN rail mounting possible, wall/direct mounting possible, font installation possible, explosion protection category for gas without, explosion protection category for dust without, width 40mm, height 125mm, depth 117mm, SIMATIC DP, Connection DP/PA-Link and ET200M IM153-2 HF for ext. Temperature range for a maximum of 12 S7-300 modules with redundancy capability, time stamping suitable for isochronous mode. Operation New features: Up to 12 modules can be used Slave initiative for Drive ES and Switch ES Extended quantity framework for HART auxiliary variables Operation of the 64-channel modules 32 signals/slot +++ Observe the compatibility information in the manual +++ The SIMATIC ET 200M is a modular and universal I/O system for the control cabinet in IP20, which can be used both as central I/O on an S7-300 and in a decentralized configuration on a PROFINET or PROFIBUS ET 200M interface module. Up to 12 IO modules can be plugged in per station. The standardized structure of all modules greatly simplifies logistics and spare parts inventory. The ET 200M can be used for both standard and safety-related applications. Up to 12 multi-channel signal (e.g. 64 digital inputs) and function modules as well as communications processors of the S7-300 can be used as I/O modules (the interface to the process). The ET 200M also supports modules with extended user data, such as HART modules with HART auxiliary variables. For easy wiring, the ET 200M offers you the stripping-free Fast Connect connection technology in addition to conventional connection technology.

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

