


Staircase light time switch - Staircase lighting timer
TLZ12G-230 V+UC

Eltako
 TLZ12G-230 V+UC
 23100831
 4010312401460 EAN/GTIN

44,02 USD excl. VAT**
 plus shipping


4-5 days* (USA)

Staircase timer switch TLZ12G-230 V+UC Electronic function with switch-off early warning, DIN rail mounting type, width in modular units 1, installation depth 58mm, number of contacts as NO contact 1, number of contacts as NC contact 0, number of contacts as changeover contact 0, control voltage 1 230 ... 230V, type of control voltage 1 AC, frequency of control voltage 1 50 ... 50Hz, control voltage 2 8 ... 230V, type of control voltage 2 AC/DC, rated switching current 1.6A, release delay 12 ... 1min, button glow lamp current 50mA, switching type 3 - and 4-wire circuit, switch-off warning flickering, current surge function selectable, downstream switching can be switched + continuous light + time extension, supply voltage 230 ... 230V, type of supply voltage AC, max. incandescent lamp load 400W, max. fluorescent lamp load (parallel compensated) 400VA, noiseless solid State relay, also for ESL and LED lamps. Switch-off pre-warning and button permanent light can be switched on. Standby loss only 0.4 watts. With ESL optimization and multifunction. Switching in the zero passage to protect the lamps. In particular, this extends the life of energy-saving lamps. Additionally with electrically isolated universal control voltage 8...230V UC. For 3- and 4-wire circuits, reconnectable, with attic lighting for 4-wire circuit. Automatic recognition of the switching type. Glow lamp current up to 50mA, depending on the ignition voltage of the glow lamps. Exact time setting 1 to 30 minutes with minute scale. Permanent light switch with the large rotary switch. After a power failure in the TLZ function setting, the lighting is switched on again if the time has not yet expired. With double connections for button and lamp, so that you can choose to connect at the top and bottom or only at the bottom. When the switch-off pre-warning is switched on, the lighting flickers about 30 seconds before the time expires and a total of 3 times at increasingly shorter intervals. When the button permanent light is switched on, buttons can be used to switch to permanent light for longer than 1 second, which is switched off automatically after 60 minutes or can be switched off with buttons for longer than 2 seconds. If the button permanent light and switch-off pre-warning are switched on, the switch-off pre-warning is only given after the permanent light has been switched off.

YOUR ADVANTAGES

WORLDWIDE TRADE
 Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide

DHL TRACK & TRACE
 Shipment tracking

COMPLAINTS HANDLING
 Obliging and 100% safely

25 YEARS OF EXPERIENCE
 In worldwide mail order

ORDER LIVE CHAT
 With order history

SHORT DELIVERY TIME
 Warehousing

REFUND
 Within 14 days

DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

