×



https://www.eibabo.us/eltako/staircase-light-time-switch-staircase-lighting-timer-1min-tlz12d-plus-eb15 710346



Staircase light time switch - Staircase lighting timer 1min TLZ12D-plus

Eltako

TLZ12D-plus 23100800 4010312401712 EAN/GTIN

39,96 USD excl. VAT**

plus **shipping**



4-5 days* (USA)

Staircase timer switch TLZ12D-plus electronic function with multifunction, mounting type DIN rail, width in modular units 1, installation depth 58mm, number of contacts as NO contact 1, number of contacts as NC contact 0, number of contacts as changeover contact 0, control voltage 1 230 ... 230V, type of control voltage 1 AC, frequency of control voltage 1 50 ... 50Hz, control voltage 2 8 ... 230V, type of control voltage 2 AC/DC, rated switching current 16A, max. switching current (cos phi = 0.6) 4A, off-delay 1 ... 1min, button glow lamp current 50mA, switching type 3- and 4-wire circuit, switch-off pre-warning flickering, current surge function selectable, subsequent switching can be switched + permanent light + time extension, supply voltage 250 ... 250V, voltage type of the supply voltage AC, max. incandescent lamp load 2300W, max. fluorescent lamp load (duo circuit) 1000VA, Max. Fluorescent lamp load (parallel compensated) 500VA, Digitally adjustable staircase light time switch with Auss switch pre-warning and button permanent light can be switched on. Standby loss only 0.7 watts. With ESL optimization and multifunction. The functions and times are entered according to the operating instructions using the MODE and SET buttons and shown digitally on the LC display. A key lock is possible. Contact switching in the zero crossing to protect the contacts and lamps. In particular, this extends the life of energy-saving lamps. The noiseless electronics do not bother the most sensitive ear - in contrast to many synchronous motors with mechanical gears. Due to the use of a bistable relay, there is no coil power loss and no heating as a result, even when switched on. After installation, wait for the brief automatic synchronization before the switched consumer is connected to the mains. Control supply and switching voltage 230V. Additionally with electrically isolated universal control voltage 8..230V UC. For 3- and 4-wire circuits, reconnectable, with attic lighting for 4-wire circuit. Automatic recognition of the

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE



In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

