



## LED floor lamp 3000K 2AP asym. - Floor lamp 1x43,6W LED not exchangeable 312279.003


**RZB**

312279.003

4051859270539 EAN/GTIN

# 1215,17 USD

excl. VAT\*\*

plus shipping bulky item



15-16 days\* (USA)

LED floor lamp 3000K 2AP asym. 312279.003 Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Socket without, Number of light heads 1, Direct/indirect components can be controlled separately, Material aluminium, Housing color black, Cover material structured plastic, Type of voltage AC, Nominal voltage 220 ... 240V, Control gear LED control gear, current-controlled, With control gear, Touch and Dim dimming, Other light distributors, High-gloss louvre design, Light distribution asymmetrical, Light emission direct/indirect, Rated service life L80/B10 at 25 °C 60000h, Protection class I, Suitable for lamp power 43.6 ... 43.6W, max. system power 92W, rated luminous flux according to IEC 62722-2-1 8700lm, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, width 340mm, height/Depth 2033mm, length 1170mm, LED floor lamps for single and double workstations. Versions with intelligent presence control and brightness sensors. Version with asymmetrical light characteristics for high uniformity in the workplace. Glare rating UGR:22, 7. Extremely narrow luminaire head. Integrated control gear. Direct and indirect light emission. LED service life 60,000 h (L80, B10). Smallest color tolerances triple MacAdam (3 SDCM). Flush membrane button for operation. Versions with a wide opening in the base plate especially for double workstations. LED floor lamp for single and double workstations. Control gear installed in the standpipe. Direct and indirect light can be switched separately. Radiation characteristics direct 60% / indirect 40%. Asymmetric light directing directly via glossy aluminum micro-louvre. Screen compatible according to EN 12464-1. Indirect light control via diffuser made of non-yellowing plastic (PMMA) with a satin finish. Flat base plate made of steel for high stability and space-saving positioning on office furniture. Footplate with wide opening 150 mm. Aluminum head and column. Luminaire powder-coated. Ergonomically optimal membrane button integrated into the light column. Bulbs (LED) included. With cable 0.75 mm² 2000 mm, black, including safety plug. Dimensions of lamp head (2x): 1012 mm x 38 mm x 28 mm Height of lamp (upper edge of lamp): 2033 mm

### YOUR ADVANTAGES


**WORLDWIDE TRADE**  
*Corporate video eibmarkt®*

**99% CUSTOMER SATISFACTION**  
*> 500,000 customers worldwide*

**DHL TRACK & TRACE**  
*Shipment tracking*

**COMPLAINTS HANDLING**  
*Obliging and 100% safely*

**25 YEARS OF EXPERIENCE**  
*In worldwide mail order*

**ORDER LIVE CHAT**  
*With order history*

**SHORT DELIVERY TIME**  
*Warehousing*

**REFUND**  
*Within 14 days*

**DATA PROTECTION**  
*Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

