

**LED emergency surface-mounted downlight 4000K 3h -
Emergency luminaire 24,5W IP40 3h 672277.002.1**



RZB
672277.002.1
4051859215691 EAN/GTIN

262,50 USD excl. VAT**
plus shipping

 15-16 days* (USA)

LED emergency surface-mounted downlight 4000K 3h 672277.002.1 Type of installation Ceiling surface-mounting, Escape route lighting function, Suitable for marking type other, Type of marking not applicable, Monitoring device automatic self-test, Switching type maintained/standby mode, Infeed decentralized (individual battery), Battery quality NiMh, Light source LED not replaceable, With lamp, Suitable for number of lamps 1, socket without, number of lamp heads 1, housing material steel, housing color white, cover material plastic opal, type of voltage AC, nominal voltage 200 ... 200V, control gear LED control gear current-controlled, light distributor without, energy efficiency class of the built-in lamp A++, A+, A (LED), protection class (IP) IP40, protection class (NEMA) other, impact resistance IK06, protection class I, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, max. system power 24,5W, rated luminous flux according to IEC 62722-2-1 2200lm, luminous flux im Standby mode 430lm, color temperature 4000 ... 4000K, nominal operating time 3 ... 3h, width 300mm, height/depth 58mm, length 300mm, type of wiring termination, number of positions 4, conductor cross-section 2.5mm², connection type plug-in connection, design continuity with general lighting. We offer a comprehensive range of safety lighting and general lighting products. Depending on the construction project, we can offer our customers integrated solutions for all areas of application. LED service life 50,000 h (L70, B10). Light guide and plastic cover made of non-yellowing PMMA. Also suitable for large ceiling heights. Installation friendly. Large luminaire spacing for escape route lighting. Unobtrusive design. Attachment housing made of sheet steel, powder-coated. Square cover plate, die-cast aluminium, powder-coated. Light guide and plastic cover made of non-yellowing plastic (PMMA). Cover plastic opal matt. Built-in operating devices. Bulbs (LED) included. Single battery system with integrated self-test. Energy efficiency class A+ I A+

YOUR ADVANTAGES

 **WORLDWIDE TRADE**
Corporate video eibmarkt®

 **99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide

 **DHL TRACK & TRACE**
Shipment tracking

 **COMPLAINTS HANDLING**
Obliging and 100% safely

 **25 YEARS OF EXPERIENCE**
In worldwide mail order

 **ORDER LIVE CHAT**
With order history

 **SHORT DELIVERY TIME**
Warehousing

 **REFUND**
Within 14 days

 **DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

