

Item Number EB10870725

https://www.eibabo.us/jung/universal-automatic-switch-movement-sensor-15m-a-17281-anm-eb10870 725



Universal automatic switch - Movement sensor 15m A 17281 ANM

×

Jung

A 17281 ANM 4011377167551 EAN/GTIN

77,84 USD excl. VAT**

plus **shipping**



15-16 days* (USA)

Automatic switch Universal A 17281 ANM Version motion detector, flush-mounted installation, networkable, creep-under protection/rear field monitoring, installation height 2.2m, max. range to one side 11m, max. frontal range 15m, detection field diameter on the floor 12m, response sensitivity adjustable, response brightness adjustable, Teach function for response brightness, dimming function with dimming insert, plastic material, thermoplastic material quality, halogen-free, suitable for degree of protection (IP) IP44, operating mode switch, min. switch-on time 2s, max. switch-on time 2min, horizontal detection angle 180 ... 180°, color anthracite, Universal automatic switch, lens type 2.20 m, detection angle: 180°, detection area: tangential movements approx. 22 x 15 m and radial movements approx. 10 x 18 m, brightness setting: approx. 5 to 500 lx and daytime operation, sensitivity: off, 25 up to 100%, run-on time: dynamic, 10 s to 60 min, operating mode switch for automatic mode, permanent on or permanent er-Off, display of the set operating mode via LED, hotel function, night light function, presence simulation, alarm function, programming of up to 16 individual switching times, installation height: 2.20 m, extension of the detection area in combination with a 3-wire extension, sensitivity and brightness threshold adjustable, Detection area can be restricted with a cover, setting the sensitivity of individual motion sensors in the device to influence the overall sensitivity, settings via smartphone and Clever Config app, indoor use, ambient temperature: - 5 to + 45 °C, for LB management applications Light item no :: 1701 SE, 1704 ESE, 1710 DE, 1711 DE, 1713 DSTE, 1723 NE and 1708 IE, for automatic switching of lighting, depending on heat movement and ambient brightness, operation with flush-mounted insert for switching or dimming or 3-wire extension to expand the detection field

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

