



**Blind + timer Bluetooth Sys.55 rwm - Intelligent control element white 536727**



**Gira**  
**536727**  
4010337027539 EAN/GTIN

**79,94 USD** excl. VAT\*\*  
plus shipping



15-16 days\* (USA)

Blind + timer Bluetooth Sys.55 rwm 536727 Application Control of electrical consumers, suitable for dimming insert, suitable for blind insert, suitable for switch insert, with cover, plastic material, thermoplastic material quality, halogen-free, other surface finish, matt finish, color white, RAL number (similar) 9010, number of buttons 2, number of actuation points 4, System 3000 blind timer and timer BT pure white, satin finish Features: Manual and time-controlled operation of e.g. B. blinds, shutters, awnings, lighting or fans. Operation and programming with a mobile end device (smartphone or tablet) via Bluetooth with the Gira Bluetooth app. Operation on System 3000 switching dimming or blind insert or auxiliary insert 3-wire. Functions on the attachment: Operation of curtains and lighting. Blocking function blocks extension operation and deactivates automatic operation. Activate automatic mode deactivate. Running time and an individual intermediate position can be saved with the System 3000 blind control insert. Switch-on brightness of lighting can be saved with System 3000 dimming insert or DALI power control unit. Adjustable night mode. Status and function LEDs do not light up continuously. Functions with the Gira Bluetooth app: operating blinds and lighting with status feedback. Display of the current curtain position or dimmer setting. Programming of up to 40 individual switching times. Blind and slat positions or switching and dimming values can be saved for each switching time. It is possible to copy switching times to other devices. Switching at sunrise or sunset (astro function). Astro time can be optimized by location determination. Astro time shift adjustable. random function. Automatic date and time update when connected to smartphone or tablet. Password protection for time programs and configuration possible (from Release 2 of the app). Storage of a blind position, blind running time, slat reversal time. Conversion to inverse operation possible for blind inserts. Maximum brightness and minimum brightness can be set when dimming is used. Optional: Sun protection and twilight functions are possible with the System 3000 Bluetooth brightness and temperature sensor. Notes: The time is updated when connected to the Gira Bluetooth app.

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

