

## Item Number EB16509638

https://www.eibabo.us/gira/knx-push-button-sensor-3-plus-2-fold-514200-eb16509638



## KNX push button sensor 3 Plus 2-fold 514200

×

Gira

514200

4010337086888 EAN/GTIN

233,80 USD excl. VAT\*\*

plus shipping



4-5 days\* (USA)

Push button 3 Plus 2-fold 514200 bus system KNX, other bus systems without, mounting type flush-mounted, with theft/dismantling protection, number of actuation points 6, number of buttons 2, with LED display, with display, material other, material quality other, surface other, Surface design not applicable, color other, with room thermostat, protection class (IP) IP20, KNX pushbutton sensor 3 Plus 2-fold system 55 commissioning rocker Features: Mounting on bus coupler 3 or bus coupler 3 external sensor. Dismantling protection through screw connection. Graphic display with backlight and various display options, e.g. E.g. temperature, time, date, alarm and information texts. Two multi-colored status LEDs per control surface. Multicolored status LED (red, green, blue) can be parameterized via the ETS. Labeling field lighting for rocker sets with labeling field. Internal temperature sensor for measuring local room temperature. Touch sensor properties: Rocker or button function adjustable for each control surface. Rocker function: switching, dimming, blind control, 1-byte value transmitter, 2-byte value transmitter, scene extension, 2-channel operation and manual fan control. Button function: switching, dimming, blind control, value transmitter 1 byte, value transmitter 2 byte, scene extension, 2-channel operation, controller extension, controller extension or controller operation: operating mode switching, (defined selection of an operating mode or switching between different operating modes for controller extension), change of the presence state, setpoint shift. Locking object for locking individual button or rocker functions. Display of an alarm message by flashing all LEDs. Multi-colored status LED (red, green, blue) can be configured globally or separately. A superimposed function can be activated via the bus, whereby the color and display information of individual status LEDs can be changed based on priority. Labeling field lighting ON, OFF, automatic switch-off or can be switched via object. Communication obj

## YOUR ADVANTAGES



**WORLDWIDE TRADE**Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



**25 YEARS OF EXPERIENCE** *In worldwide mail order* 



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

