



KNX push button sensor 3 comfort 6-fold 513600


Gira

513600

4010337086871 EAN/GTIN

189,71 USD

 excl. VAT**

plus shipping



4-5 days* (USA)

KNX push-button sensor 3 comfort 6-fold 513600 bus system KNX, other bus systems without, type of installation flush-mounted, with theft/dismantling protection, number of actuation points 12, number of buttons 6, with LED display, material quality other, surface other, version of Surface not applicable, other color, with room thermostat, protection class (IP) IP20, KNX push button sensor 3 comfort 6-fold (3+3) system 55 commissioning rocker Features: Installation on bus coupler 3. Dismantling protection by screwing. Two multicolored status LEDs per control surface. Integrated temperature sensor for measuring and forwarding the local room temperature. Rocker or button function can be set for each control surface. Rocker function: switching, dimming, shutter control, 1-byte value transmitter, 2-byte value transmitter, scene extension and room temperature controller extension. Button function: switching, dimming, shutter control, 1-byte value transmitter, 2-byte value transmitter, scene extension and room temperature controller extension. Controller extension: Operating mode changeover with normal and high priority, defined selection of an operating mode, changeover between different operating modes, change in presence status, setpoint shift. Blocking object for blocking individual button or rocker functions. Display of an alarm message by flashing all LEDs. Multicolored status LED (red, green, blue) is configurable globally or individually. A higher-level function can be activated via the bus, whereby the color and display information of individual status LEDs can be changed depending on the priority. Communication object for controlling the brightness of the status LED and for lighting the labeling field (e.g. to reduce the brightness in bedrooms at night). Labeling field lighting for rocker sets with labeling field. Labeling field lighting ON, OFF, automatic switch-off or switchable via object. Notes: Professional lettering via the Gira lettering service The push button sensor is supplied with a program-neutral commissioning rocker. The appropriate rocker set for the switch range must be ordered separately.

YOUR ADVANTAGES


WORLDWIDE TRADE

Corporate video eibmarkt®


99% CUSTOMER SATISFACTION

> 500,000 customers worldwide


DHL TRACK & TRACE

Shipment tracking


COMPLAINTS HANDLING

Obliging and 100% safely


25 YEARS OF EXPERIENCE

In worldwide mail order


ORDER LIVE CHAT

With order history


SHORT DELIVERY TIME

Warehousing


REFUND

Within 14 days


DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

