



**Universal rotary dimmer comfort (R,L,C,LED), soffr. -  
Dimmer flush mounted 20...420VA 296110**



**Berker**  
296110  
4011334510147 EAN/GTIN

**74,78 USD** excl. VAT\*\*  
plus shipping

 **4-5 days\* (USA)**

Universal rotary dimmer comfort (R,L,C,LED), soffr. 296110 Composition of basic element, operation type rotary/push button, dimming leading edge, dimming trailing edge, load type universal and LED retrofit, extension input, light value memory, type of installation flush-mounted, type of attachment claw attachment, material other, material quality other, halogen-free, surface untreated, suitable for protection class (IP) IP20, rated voltage 230 ... 230V, frequency 50 ... 60Hz, rated power 20 ... 420VA, connection type screw terminal, core cross section 0.5 ... 4mm², device width 71mm, device height 71mm, device depth 43mm, min. depth of the device box 27mm, Universal rotary dimmer comfort (R, L, C, LED), soft locking, light control. Arsys program description (long text) Switch program made of Duroplast, scratch-resistant, in the colors polar white (similar to RAL 9010), white (similar to RAL 1013), glossy brown (similar to RAL 8011). Additional materials Stainless steel, light bronze painted aluminum and gold anodised aluminum available. Frame 1x - 5x, different design for vertical and horizontal assembly. Rectangular basic shape and rounded corners with a 4.5 mm radius of curvature, with a spherical (500 mm diameter) curved geometry and glossy or matt surfaces. Rockers/covers with an edge length of 52.5 mm x 71 mm and rounded corners with a radius of 2 mm. Installation devices can be used in some cases with a separate sealing set that is water-protected UP IP 44. Possibility of inscription partly possible by inscribable rockers/covers. Abrasion-resistant identification of the products by printing. Can be illuminated according to workplace regulations. The material used is halogen-free and UV-stable, the surfaces are easy to clean and are resistant to disinfectants. Over 200 applications.

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

