



## Engine starter - Reversing starter combination 5,5kW 3RK1325-6LS41-1AA3



**Siemens**  
**3RK1325-6LS41-1AA3**  
 4011209823754 EAN/GTIN

**881,34 USD** excl. VAT\*\*  
 plus shipping



15-16 days\* (USA)

Motor starter 3RK1325-6LS41-1AA3 Type of motor starter Reversing starter, With short-circuit release, Rated control supply voltage  $U_s$  at DC 20.4 ... 28.8V, Type of voltage for actuation DC, Rated operational power at AC-3, 400 V 5.5kW, Rated operational current  $I_e$  12A, Rated operational current at AC-3, 400 V 12A, overload release current setting 1.5 ... 12A, tripping class other, connection type main circuit other, design of electrical connection for auxiliary and control circuit other, type of coordination according to IEC 60947-4-3 class 1, degree of protection (IP) IP65, supports protocol for ASI, width 294mm, height 215mm, depth 159mm, SIRIUS motor starter M200D AS-i communication: AS-Interface reversing starter standard mechanically switching AC-3, 5.5 kW / 400 V 1.5 A... 12.00 A electronic thermistor overload protection: THERMOCLICK / PTC with braking contact 400 V AC 4DI / 1DO AS-i Han Q4/2 - Han Q8/0 motor starter SIRIUS M200D for starting, monitoring and protecting motors and consumers for use in the field, e.g. in conveyor technology. The robust motor starters with a high degree of protection for AS-Interface are easy to configure and, thanks to the modular starter concept and pre-assembled cables, can be installed, commissioned and replaced quickly and without errors when servicing is required. The integration of associated sensors is supported. The use of the devices increases system availability thanks to a comprehensive diagnostics concept and sophisticated system monitoring. The Motor Starter ES software is available for configuration, commissioning, operation and diagnostics. The motor starters are approved worldwide (e.g. IEC and UL/CSA) and IE3/IE4ready. Available as direct or reversing starters with different motor current ranges, optionally with electromechanical or electronic switching, optionally with brake control or local manual on-site operator panel. On A comprehensive range of accessories suitable for all M200D motor starters is available, eg pre-assembled cables. SIRIUS M200D - The robust motor starter for decentralized drive solutions.

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
 Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
 > 500,000 customers worldwide



**DHL TRACK & TRACE**  
 Shipment tracking



**COMPLAINTS HANDLING**  
 Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
 In worldwide mail order



**ORDER LIVE CHAT**  
 With order history



**SHORT DELIVERY TIME**  
 Warehousing



**REFUND**  
 Within 14 days



**DATA PROTECTION**  
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
 eibabo® electronics cheap online order  
 eibabo® electric appliances buy online

