



Direct starter combination 1,5kW 3RA6400-2CB42


Siemens

3RA6400-2CB42

4011209714847 EAN/GTIN

578,83 USD excl. VAT**
plus shipping



15-16 days* (USA)

Direct starter DC 24 V, 1-4A 3RA6400-2CB42 Type of motor starter direct starter, with short-circuit release, type of voltage for actuation DC, rated operational power at AC-3, 400 V 1.5kW, rated operational current Ie 4A, overload release current setting 1 ... 4A, number of Auxiliary contacts as NO contacts 0, number of auxiliary contacts as NC contacts 0, ambient temperature, upper limit without restrictions 40°C, tripping class adjustable, connection type main circuit spring-loaded connection, design of electrical connection for auxiliary and control circuit spring-loaded connection, type of coordination according to IEC 60947-4-3 class 2, number the indicator light 3, degree of protection (IP) IP20, degree of protection (NEMA) other, supports protocol for other bus systems, width 45mm, height 191mm, depth 165mm, SIRIUS compact starter direct starter for IO-Link 690 V DC 24 V 1...4 A IP20 Main circuit connection: Spring-loaded connection Control circuit connection: Spring-loaded connection Compact starter for IO-Link SIRIUS 3RA64 for direct starting of rotary current standard motors up to 32 A. The devices combine the functions of circuit breakers, contactors and electronic overload relays and have a very high level of operational safety. A small variance simplifies the logistics. The compact design saves space in the control cabinet. The devices can be integrated into the Totally Integrated Automation concept via the integrated IO-Link interface and supply extensive diagnostic data to the higher-level controller. Thanks to detachable clamps, easy replacement is possible. The devices are approved worldwide (eg IEC and UL/CSA). The compact starters are available as direct or reversing starters and are available with different setting ranges. Designed for DC operation, they are available with screw or spring-type terminals. In addition to the 3RA68 infeed system, operator panels, auxiliary contacts and terminals as well as connecting cables are available. Simple, efficient, always up-to-date - the SIRIUS modular system.

YOUR ADVANTAGES


WORLDWIDE TRADE

Corporate video eibmarkt®


99% CUSTOMER SATISFACTION

> 500,000 customers worldwide


DHL TRACK & TRACE

Shipment tracking


COMPLAINTS HANDLING

Obliging and 100% safely


25 YEARS OF EXPERIENCE

In worldwide mail order


ORDER LIVE CHAT

With order history


SHORT DELIVERY TIME

Warehousing


REFUND

Within 14 days


DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

