

Item Number EB17206279

https://www.eibabo.us/eaton/load-break-switch-32a-3-pole-safety-switch-3-p-15kw-p1-32-m4-svb-eb17 206279

Load-break switch 32A, 3-pole - Safety switch 3-p 15kW P1-32/M4/SVB





P1-32/M4/SVB 172865 4015081694457 EAN/GTIN



plus **shipping**



15-16 days* (USA)



Load-break switch 32A, 3-pole P1-32/M4/SVB Design as a main switch Design as a maintenance/repair switch Design as an EMERGENCY STOP device Number of switches 1 Max. rated operating voltage Ue at AC 690V Rated operating voltage 690 ... 690V, rated uninterrupted current Iu 32A, rated uninterrupted current at AC-23, 400 V 32A, rated uninterrupted current at AC-21, 400 V 32A, rated operational power at AC-3, 400 V 15kW, rated short-time withstand current Icw 0.64kA, rated operational power at AC-23, 400 V 15kW, switching capacity at 400 V 15kW, rated conditional short-circuit current Iq 80kA, number of poles 3, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as changeover contact 0, device design built-in device fixed installation, suitable for floor mounting, suitable for intermediate construction, colour of the actuating element red, design of the actuating element door-coupling rotary drive, lockable, connection type main circuit screw connection, protec rt (IP), front IP65, degree of protection (NEMA) other, main switch, range: main switch, maintenance switch, repair switch, type identifier: P1, STOP function: EMERGENCY STOP function, with red rotary handle and yellow locking ring, note: with metal axis for Control cabinet depth 400 mm, information on scope of delivery: Auxiliary switch contact or neutral conductor can be retrofitted., 3-pole, lockability: lockable in 0 position, degree of protection: front IP65, design: intermediate construction, rated operational power AC-23A, 50 - 60 Hz 400 V: P = 15 kW, rated continuous current: Iu = 32 A, standards and regulations: IEC/EN 60947, VDE 0660, IEC/EN 60204, load-break switch according to IEC/EN 60947-3

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

