



Position switch 1NO+1NC - Adjustable rotary lever switch IP65 LS-11S/RLA-M12A



Eaton
 LS-11S/RLA-M12A
 178143
 4015081734665 EAN/GTIN

43,49 USD excl. VAT**
 plus shipping



15-16 days* (USA)

Position switch 1NO+1NC LS-11S/RLA-M12A Sensor width 31mm, sensor diameter 0mm, sensor height 86mm, sensor length 33.5mm, rated operational current Ie at AC-15, 24 V 6A, rated operational current Ie at AC-15, 125 V 6A, rated operational current Ie at AC-15, 230 V 6A, rated operational current Ie at DC-13, 24 V 3A, rated operational current Ie at DC-13, 125 V 0.6A, rated operational current Ie at DC-13, 230 V 0.3A, switching function snap-action contact, positive opening, number of safety-related auxiliary contacts 1, number of contacts as NC contacts 1, number of contacts as NO contacts 1, number of contacts as change-over contacts 0, version of the interface without, version of the interface for safety-related communication without, cuboid housing design, material of the housing plastic, coating housing other, design of the actuating element adjustable swivel lever, alignment of the actuating element other, design of the electrical connection other, Geei magnet for safety functions, explosion protection category for gas without, explosion protection category for dust without, ambient temperature during operation 25 ... 70 °C, degree of protection (IP) IP65, degree of protection (NEMA) 4X, position switch, basic function: position switch, safety Position switch, type identifier: LS(M)-..., assortment: adjustable roller lever, degree of protection: IP66, scope of delivery: with integrated M12 connector, equipment: complete device, ambient temperature: -25 - +70 °C, snap-action contact element: yes, contacts S = NO contact: 1 NO, contacts NC = NC contact: 1 NC, note: = safety function, with positive opening according to IEC/EN 60947-5-1, positive opening (ZW): yes, housing cover color: yellow, housing: plastic, connection type: cage clamp, Cage-Clamp is a registered trademark of Wago Kontakttechnik, 32432 Minden., Accessories for the Cage-Clamp connection from Wago: Insertion bridge, grey, Wago order no. 264-402, standards and regulations: IEC/EN 60947

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

