

Item Number EB12101706

×

https://www.eibabo.us/eaton/power-contactor-55kw-400v-ac-magnet-contactor-115a-190...240vac-0vd c-dilmc115-rac240-eb12101706



Power contactor 55kW, 400V AC - Magnet contactor 115A 190...240VAC 0VDC DILMC115(RAC240)

Eaton DILMC115(RAC240) 239736 4015082397364 EAN/GTIN

440,67 USD excl. VAT**

plus shipping



Power contactor 55kW, 400V AC DILMC115(RAC240) rated control supply voltage Us at AC 50 Hz 190 ... 240V, rated control supply voltage Us at DC 0V, type of voltage for actuation AC, rated operational current le at AC-1, 400 V 160A, rated operational current le at AC-3, 400 V 115A, rated operational power at AC-3, 400 V 55kW, rated operational current le at AC-4, 400 V 55A, rated operational power at AC-4, 400 V 28kW, rated operational power NEMA 74, 6kW, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as NC contact 0, connection type main circuit screw connection, number of NC contacts as main contacts 0, number of NC contacts 3, power contactor, application: power contactor for motors, power contactors up to 170 A, 3- pole, Utilization category: AC-1: non-inductive or weakly inductive load, resistance furnaces, AC-3: squirrel-cage motors: starting, switching off during operation, AC-4: cage Ignition motors: starting, counter-current braking, reversing, jogging, connection technology: spring-loaded terminals, Note: also suitable for motors of efficiency class IE3, IE3-capable devices are marked with the logo on the packaging. Description: spring-loaded terminals on the auxiliary and control line connections, poles : 3-pole, rated operational current AC-3 a80 V 400 V: Ie= 115 A, rated operational current AC-1 conventional thermal current, 3-pole, 50 - 60 Hz open at 40 °C: Ith = Ie= 160 A, encapsulated: Ith= 115 A, rated operational current 1-pole open: Ith= 325 A, encapsulated: Ith= 285 A, max. rated operational power of three-phase motors 50 - 60 Hz AC-3 220 V 230 V: P= 37 kW, 380 V 400 V: P= 55 kW, 660 V 690 V: P= 90 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P= 17 kW, 380 V 400 V: P= 28 kW, 660 V 690 V: P= 43 kW, can be combined with auxiliary switches: DILM150-XHIC(V)..., DILM1000-XHIC..., Notes: contact el

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

