

Item Number EB13909327

https://www.eibabo.us/eaton/power-contactor-3-pole-magnet-contactor-150a-190...240vac-0vdc-dilmc150-rac240-eb13909327



Power contactor 3-pole - Magnet contactor 150A 190...240VAC 0VDC DILMC150(RAC240)



Eaton

DILMC150(RAC240) 239751 4015082397517 EAN/GTIN

571,24 USD excl. VAT**

plus shipping



15-16 days* (USA)

Power contactor 3-pole DILMC150(RAC240) Rated control supply voltage Us at AC 50 Hz 190 ... 240V, Rated control supply voltage Us at AC 60 Hz 190 ... 240V, Rated control supply voltage Us at AC 60 Hz 190 ... 240V, Rated control supply voltage Us at DC 0V, Type of voltage for actuation AC, Rated operational current le at AC-1, 400 V 190A, Rated operational current le at AC-3, 400 V 150A, rated operational power at AC-3, 400 V 75kW, rated operational current le at AC-4, 400 V 65A, rated operational power at AC-4, 400 V 33kW, rated operational power NEMA 93kW, number of auxiliary contacts as NC contact 0, connection type main circuit screw connection, number of NC contacts as main contacts 3, power contacts as NC contact 0, connection type main circuit screw connection, number of NC contacts as main contacts 3, power contactor of motors, power contactors up to 170 A, 3-pole, utilization category: AC-1: Non-inductive or weakly inductive load, resistance furnaces, AC-3: squirrel-cage motors: starting, switching off during run, AC-4: squirrel-cage motors: starting, reversing, jogging, Connection technology: Spring-loaded terminals, Note: Also suitable for motors of efficiency class IE3., IE3-capable devices are marked with the logo on the packaging., Description: Spring-loaded terminals on the auxiliary and control line connections, Poles: 3-pin , Rated operational current AC-3 380 V 400 V: Ie= 150 A, Rated operational current AC-1 conventional thermal current ac-1 conventional thermal current 1-pole open: Ith= 400 A, encapsulated: Ith= 360 A, max. rated operational power of three-phase motors 50 - 60 Hz AC-3 220 V 230 V: P= 96 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P= 20 kW, 380 V 400 V: P= 96 kW, 660 V 690 V: P= 96 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P= 20 kW, 380 V 400 V: P= 48 kW, 660 V 690 V: P= 96 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P= 20 kW, 380 V 400 V: P= 96 kW, 660 V 6

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliv

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

