Item Number
EB15506852

26.04.2024/12:45

https://www.eibabo.us/phoenix/decentralized-i-o-device-16-inputs-outputs-fieldbus-digital-module-16-in-16-out-axleeipdio16m...-eb15506852

Decentralized I/O device 16 inputs/outputs - Fieldbus digital module 16 In / 16 Out AXLEEIPDIO16M...

Phoenix
AXLEEIPDIO16M126P
2701494
4046356763486 EAN/GTIN

471,27 USD excl. VAT**
plus **shipping**

15-16 days* (USA)

Fieldbus digital module 16 In / 16 Out, Supply voltage for DC 18..31..2 V, Voltage type of the supply voltage DC, Number of digital inputs 16, Number of digital outputs 16, Digital inputs configurable no, Digital outputs configurable no, Input current for signal 1 0,003 mA, Permissible voltage at the input 24..30 V, Type of input voltage DC, Type of digital output without, Output current 0.5 A, Permissible voltage at the output 18..31..2 V, Type of output voltage DC, Short-circuit protection, outputs available yes, Number of HW interfaces, other 2, With optical interface no, Supports protocol for TCP/IP no, Supports protocol for PROFIBUS no, Supports protocol for CAN no, Supports protocol for INTERBUS no, Supports protocol for ASI no, Supports protocol for KNX no, Supports protocol for MODBUS no, Supports data highway protocol no, Supports protocol for DeviceNet no, Supports protocol for SUCONET no, Supports protocol for LON no, Supports protocol for PROFINET IO no, Supports protocol for PROFINET CBA no, Supports protocol for SERCOS no, Supports protocol for Ethernet/IP yes, Supports protocol for DeviceNet Safety no, Supports protocol for INTERBUS safety no, Supports protocol for PROFIsafe no, Supports protocol for SafetyBUS p no, Supports protocol for other bus systems yes, IO link master no, System component yes, Degree of protection (IP) IP65, Type of electrical connection other, Delay time with signal change 0ms, Mounting rail installation possible no, Wall/direct mounting possible yes, Front installation possible no, Rack mounting possible no, Suitable for safety functions no, SIL according to IEC 61508 without, Performance level according to EN ISO 13849-1 without, Associated equipment (Ex ia) no, Associated equipment (Ex ib) no, Explosion protection category for gas without, Explosion protection category for dust other, Width 60 mm, Height 185 mm, Depth 30.5 mm

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online