


SIRIUS soft starter 200-480 V 470 A - Soft starter 470A 110...250VAC 3RW50766TB14


Siemens
3RW50766TB14
 4047621061252 EAN/GTIN

3474,01 USD excl. VAT**
 plus shipping



15-16 days* (USA)

SIRIUS soft starter 200-480 V 470 A 3RW50766TB14 Rated operating current Ie at 40 °C Tu 470A, rated operating voltage Ue 200 ... 480V, rated power three-phase motor, standard circuit, at 230 V 132kW, rated power three-phase motor, standard circuit, at 400 V 250kW, function a direction of rotation, Internal bridging, rated ambient temperature without derating 40°C, rated control supply voltage Us at AC 50 Hz 110 ... 250V, rated control supply voltage Us at AC 60 Hz 110 ... 250V, voltage type for actuation AC, integrated overload protection of the motor, tripping class adjustable, protection class (IP) IP00, SIRIUS soft starter 200-480 V 470 A, AC 110-250 V screw terminals thermistor input SIRIUS 3RW50 Basic Performance soft starter for simple applications for the gentle starting and stopping of three-phase asynchronous motors. Continuously variable starting, reducing current peaks, avoiding mains voltage fluctuations during startup, relieving the load on the power supply network, reducing the mechanical load on the drive, significant space and wiring savings compared to star-delta starters and frequency converters, maintenance-free switching and extremely easy handling. The integrated bypass enables the very compact design, saves energy and ensures less heating in the control cabinet. Intelligent monitoring functions protect the soft starter from overheating and the motor from overload. You can also limit the current to an adjustable maximum value during startup. The innovative Soft Torque function ensures gentle engine startup. With the integrated remote reset, you can quickly and easily troubleshoot problems remotely. Worldwide approvals (e.g. IEC and UL/CSA) also for potentially explosive applications (ATEX or IEC Ex). The Basic Performance 3RW50 soft starters are available for networks up to 600 V in a power range of up to 315 kW with 24 V or 110-250 V control supply voltages and consistently with screw and spring-loaded connections. Different device variants are available for analog output and thermistor motor protection. Optional communication modules enable connection via PROFINET, PROFIBUS and Modbus TCP. Various HMI modules are available for installation in the control cabinet door. The 3RW50 soft starters replace the proven 3RW40 series (sizes S6 to S12). SIRIUS 3RW5 soft starter - as flexible as your task.

YOUR ADVANTAGES


WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

