×



Item Number EB13262604

https://www.eibabo.us/ledvance/led-floodlight-3000k-downlight-spot-floodlight-flpfm125w3000ksym100-eb13262604



LED floodlight 3000K - Downlight/spot/floodlight FLPFM125W3000KSYM100

.PFM125W3000KSYM100

LEDVANCE

FLPFM125W3000KSYM100 4058075423695 4058075423695 EAN/GTIN

219,32 USD excl. VAT**

plus shipping



15-16 days* (USA)

LED floodlight 3000K FLPFM125W3000KSYM100 Energy efficiency class of the built-in light source A++, A+, A (LED), Suitable for surface mounting, Suitable for wall mounting, Pivotable adjustability, LED light source cannot be replaced, With light source, Housing material aluminium, Powder-coated surface, Housing color black, Material of cover glass opal, type of voltage AC, nominal voltage 100 ... 277V, nominal LED current at constant current 630 ... 630mA, ballast electronic ballast, with ballast, without dimming function, light distributor reflector, beam angle unshielded/diffuse, light emission direct, total harmonic distortion (THD) 19, rated service life L70/B10 at 25 °C 70000h, rated service life L80/B10 at 25 °C 55000h, rated service life L90/B10 at 25 °C 35000h, rated service life L90/B50 at 25 °C 35000h, degree of protection (IP) IP65, impact strength IK08, protection class I, rated ambient test Temperature according to IEC62722-2-1-30 ... 50 °C, max. system power 125W, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, luminous flux 13750 ... 13750Im, rated luminous flux according to IEC 62722-2-1 13750Im, lamp efficacy 110Im/W, power factor 0.9, width 290mm, height/depth 59mm, length 1000mm, type of wiring termination, number of poles 3, connection type other, luminous efficacy 110Im/W, glow wire test according to IEC 60695-2-11 650 °C - 30 s, photobiological safety according to EN 62471 RG1, color consistency (McAdam ellipse) SDCM5, versatile floodlight with 125 W power consumption. Product features: Reflector-based, symmetrical light distribution with a beam angle of 100 ° x 100°. Integrated ballast with a wide input voltage range, suitable for 100 - 277 VAC. Surge protection: up to 6kV (L/N-PE), 4kV (LN). Mounting bracket with 30° angle and large rotation range. Climate membrane for optimized air exchange, with a consistently high IP protection level. Pre-installed, flexible cable (H05RN-F) with 1 m length, 3 x 1.0 mm² crimped. Product advantages: bright, robust an

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTIONGuarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

