



**Motion detector white - Movement sensor 280° 5m
DEFENSOR #EM10025396**



ESYLUX
DEFENSOR #EM10025396
EM10025396
4015120025396 EAN/GTIN

111,96 USD excl. VAT**
plus shipping



4-5 days* (USA)

Motion detector white DEFENSOR EM10025396 Version motion detector, sensor type passive infrared, creep-under protection/rear field monitoring, scanning angle 280°, optimum mounting height 3m, stairwell monitoring, max. range to one side 20m, max. frontal range 5m, detection field diameter on the floor 40m, remote controllable, sensitivity adjustable, Response brightness adjustable, Teach function for response brightness, Suitable for ceiling mounting, Suitable for wall mounting, Surface mounting type, Connection type screw terminal, Plastic material, Thermoplastic material quality, Surface untreated, Surface finish matt, Color white, RAL number (similar) 9003, Degree of protection (IP) IP55, impact resistance IK07, type of voltage AC, frequency 50 ... 60Hz, nominal voltage 240V, min. duty cycle 60s, max 0°, swivel range sensor, vertical 0°, response brightness 2 ... 2000lx, max. switching capacity 2300W, suitable for C-load, temperature -25 ... 50°C, number of switching zones 1, max. inrush current 800A, extension input, width 92mm, height 138mm, depth 108mm, Motion detector with 280° field of detection and Ø 40 m range (tangential). Time-dependent operating modes. Intelligent protection against vandalism and sabotage (light on in the event of a malfunction). 360° creep-under protection for complete detection (can be deactivated). Follow-up time dependent on walking direction. Password protection against unauthorized parameterization. Immediate operational readiness with factory settings. Easy parameterization via ESY-Pen and ESY-App. Flexible sensor head for wall and ceiling mounting. Fast installation with plug-in terminals up to 2.5 mm 2. Wiring through with double membrane cable entry also for underground cables with Ø 15 mm. Masking of detection areas with the enclosed lens mask that can be cut to size. Sensitivity of detection areas can be customized. Very high overvoltage protection (surge 2 kV, burst 4 kV). Zero crossing switching for relay-friendly switching of LEDs. button input. impulse function. Special base for inside and outside corner mounting as an accessory.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

