

**Light scene sensor. 8x comfort polar white - KNX touch sensor 8-fold 75168699****Berker**
75168699
4011334257240 EAN/GTIN**136,09 USD** excl. VAT**
plus shipping

15-16 days* (USA)

Light scene push button sensor 8-fold comfort pws 75168699 bus system KNX, other bus systems without, mounting type flush-mounted, with theft/dismantling protection, number of actuation points 8, number of buttons 4, with LED display, material plastic, material quality thermoplastic, surface untreated, surface design matt, Color white, RAL number (similar) 9010, degree of protection (IP) IP20, light scene push button sensor 8-fold comfort B.IQ polar white, matt. Comfort B.IQ light scene pushbutton sensor with dismantling protection, with one operating and eight status LEDs. Flush installation. When the button is pressed, the comfort light scene pushbutton sensor sends telegrams to the instabus EIB, which trigger corresponding functions in the actuators. Depending on the application loaded, up to 8 light scenes can be saved and called up again or 4 telegram sequences with a maximum of 8 outputs can be generated. User module for plugging onto the Up bus coupling with disassembly protection by screwing to the bus coupling unit. An LED is assigned to each actuating button, the function of which can be determined via the parameter settings. Each key can be freely configured. Depending on the selected application and parameter settings for controlling switching, dimming or blind actuators and as a value transmitter in connection with scenes and telegram sequences. The push button sensor has 2 operating levels that can be set manually. The equipment can be set in the 2nd operating level. Additional sensors can be omitted. An alarm object enables an alarm command to be sent if the user module is separated from the bus coupler. Application properties: light scene/dimming: blocking function via object, cascade operation of several light scene push-button sensors, actuation display: variable lighting duration of the status LED, second operating level: setting the lights, telegrams can be sent at different times, dimming function can be set, outputs can be taken separately from light scenes, possibility of division of the 8 outputs in two independent light scene areas, single-surface actuation, dimming function, extension function. Telegram sequence: alarm function, 4 telegram sequences, random operation, endless operation, 8 outputs, outputs can be blocked, single-surface actuation, dimming function, extension function.

YOUR ADVANTAGES**WORLDWIDE TRADE**
Corporate video eibmarkt®**99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide**DHL TRACK & TRACE**
Shipment tracking**COMPLAINTS HANDLING**
Obliging and 100% safely**25 YEARS OF EXPERIENCE**
In worldwide mail order**ORDER LIVE CHAT**
With order history**SHORT DELIVERY TIME**
Warehousing**REFUND**
Within 14 days**DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

