

Item Number EB10865223

×

https://www.eibabo.us/merten/universal-led-dimmer-module-black-dimmer-flush-mounted-4...200va-me g5300-0001-eb10865223



Universal LED dimmer module black - Dimmer flush mounted 4...200VA MEG5300-0001

Merten MEG5300-0001 4042811185107 EAN/GTIN

## 57,36 USD excl. VAT\*\*

plus **shipping** 



Universal LED dimmer module black MEG5300-0001 Composition of basic element with complete housing, touch operation, phase cut dimming, phase cut dimming, universal load type and LED retrofit, extension input, light value memory, can be used with button, flush-mounted installation type, other type of attachment, plastic material, thermoplastic material quality, halogen-free, Surface untreated, design of the surface matt, color black, RAL number (similar) 0, suitable for degree of protection (IP) IP20, rated voltage 230 ... 230V, frequency 50 ... 50Hz, rated power 4 ... 200VA, connection type Screw terminal, core cross-section 2.5 ... 2.5mm<sup>2</sup>, device width 40mm, device height 45mm, device depth 20mm, min. depth of device socket 46mm, for ohmic, inductive or capacitive loads, e.g. B. dimmable LED lamps, incandescent lamps, dimmable wound transformers or electronic transformers. (Leading or trailing edge). The universal dimmer module automatically recognizes the connected load. Do not connect mixed loads. The dimmer module is controlled with mechanical buttons in parallel operation. When installing the dimmer module in combination with a button, a deep (60 mm) installation box must be used. With screw terminals. Rated voltage: AC 230 V, 50 Hz. Switching capacity: LED lamps: 4-100 VA (RC mode). 4-20VA (RL LED mode). Incandescent lamps: 5-200 W. Halogen lamps: 5-150 W (230 V). 5-200 VA (NV with dimmable wound transformer). 5-200 VA (NV with dimmable electronic transformer). Neutral conductor: not required. Connection terminals: Screw terminals for max. 2.5 mm<sup>2</sup>. Protection: 16 A circuit breaker. Dimensions: 45x40x21 (HxWxD). Properties: -short-circuit proof. overheat resistant. soft start. memory function. automatic load detection. Min. / Max. limit adjustable. Operating mode RL-LED mode adjustable. Note: Information on the subject of dimming LED lamps is available on the Internet under Merten Dimmertest. . Color: Black.

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

