



**Ballast 2x28/54W 220-240V - Electronic ballast 2x169W
QTI 2X28/54/220-240D**



LEDVANCE
QTI 2X28/54/220-240D
4050300870717
4050300870717 EAN/GTIN

79,62 USD excl. VAT**
plus shipping



4-5 days* (USA)

Electronic ballast QTI 2X28/54/220-240D electronic version, multiwatt version, dimming 1-10 V, for lamp type HI, for lamp type T7, for lamp type T16, for lamp type T16-R, for lamp type T26, for lamp type TR, for lamp type TU, for lamp type TC-D, for lamp type TC-DD, for lamp type TC-DEL, for lamp type TC-F, for lamp type TC-L, for lamp type TC-S, for lamp type TC-SEL, for lamp type TC-T, For lamp type TC-TEL, suitable for lamp power (2-lamp) 28... 54W, suitable for number of lamps 2... 2, suitable for lamp power 169... 169W, nominal voltage 220... 240V, housing metal housing, degree of protection (IP) IP20, protection class I, length 423mm, width 30mm, height 21mm, product family advantages: Same luminous flux with direct and alternating voltage. Perfect lamp warm start for motion sensor applications. Dimming amalgam lamps without flickering or shortening their lifespan. Highest efficiency through cut-off technology. Automatic restart after lamp replacement. Ballasts meet the MINERGIE standard thanks to very low standby consumption. Configurable backup power properties. Product family features: Control via 110 V interface. Supply voltage: 220240 V. Mains frequency: 0 Hz 50 Hz 60 Hz. Mains voltage: 198264 V. Dimming range: 1100% luminous flux. Lamp start: within 0.6 s. Lifetime: 100,000 h (at T = 65 °C at Tc). Automatic safety shutdown in the event of a lamp defect and at the end of the lamp's life (EoL T.2). Energy Efficiency Index EEI: A1 BAT. Overtemperature protection through thermal management at high temperatures. Safety: according to EN 61347-2-3. Areas of application: Suitable for emergency power installations. Industry. Open-plan offices, corridors or storage rooms. Public buildings. Suitable for luminaires of protection class I.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

